

AMCO

MANUFACTURING, INC.



Maintenance-Free
Gang Bearings



TERRACING PLOW

A tough tool for building the best terraces.

With the AMCO Manufacturing TJ3 Terracing Plow, you can build 1,000 feet of terraces or more per hour, working within Soil Conservation Service specifications. This terracing plow design is unique to AMCO and can be integrated with your own equipment and operated by your own laborers, saving you time and money when compared to the same terraces built with bulldozers, scrapers, and other large earth-moving equipment.

The AMCO Terracing Plow builds and packs the terrace with multiple trips through the field. In addition to building new terraces, this AMCO tool is effective in refurbishing older terraces.

- › 1½" square, high-carbon cold-rolled steel axles
- › Extra-heavy-duty, 7" x 7" x ¾" main frame with category III three-point hitches; is quick-hitch compatible
- › Disc gangs feature maintenance-free bearings with three-year warranty; bearings eliminate possibility of contamination and need for re-lubrication
- › Features 26" x ¼" cutout or smooth blades with 10" backup blades on inside and outside blades, as well as two 20" x ¼" end blades with 10" backup blades
- › ¾" x 6½" x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2½" x 2½" square tubing. The scrapers are attached to the 2½" x ½" thick arms with heavy-duty u-bolts
- › Two 4" x 16" independent 3,000 PSI hydraulic cylinders and four ¾" diameter hoses to mount from hydraulic cylinders to tractor
- › Tilt indicator that allows positive setting of gangs from driver's seat at desired tilt; hydraulically controlled from 18 degrees down to 43 degrees up
- › Gang angle adjustable from 21 to 29 degrees

FEATURES



PRODUCT PERFORMANCE GUARANTEE—Repair, Replace, or Refund: AMCO Guarantees Performance. The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

Below: Tilt indicators show accurate settings of gang tilt and enable both gangs to be set the same.



Left: Move gangs forward or back to control the cutting angle.

Right: AMCO's Shock Absorber Bearing Risers allow the gang to move upward and back to relieve shock when the disc blades encounter an obstacle in the ground.



Above: Two parking stands allow you to park your Terracing Plow in the upright position for easy connect and disconnect.



Above: A rear view of the Terracing Plow.



MANUFACTURING, INC.

800 S. Industrial Parkway
P. O. Box 1107
Yazoo City, MS 39194

Toll free: 800-748-9022
662-746-4464
Fax: 662-746-6825

Web: www.amcomfg.com
Facebook: www.facebook.com/AMCOManufacturingInc
Email: sales@amcomfg.com

TJ3 Terracing Plow

Model	Cutting Width	No. of Disc Blades	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs.*
TJ3-1826	16'10"	18	6	176-270	3,212

**To calculate weight/blade, divide the approximate weight of the model by the number of disc blades. Specifications for all models subject to change without notice.*



**TOUGH
TILLAGE
TOOLS**