


AMCO

MANUFACTURING, INC.



Guaranteed for two full years.



G2 WHEEL OFFSET HARROWS

Dependable and rugged: That's the G2

Our most massive tool, the G2 Wheel Offset Harrow features 12½" blade spacing and measures 54" from the top of the frame to the bottom of the blades. Weighing from 10,179 to 14,821 pounds, it is perfect for challenging conditions like breaking up new ground and heavily wooded site preparation. The G2 is also built to withstand the toughest construction industry tasks. To handle the G2 power, AMCO designed an oversized 5" x 16" x 2½" hydraulic cylinder with special clevis that lifts the harrow into transport position on dual wheels.

- › Features standard 32" x ¾" cutout blades with back-up blades on 12½" spacing; welded spacer spools provide longer life
- › Other blade options: impressive 36" x ½" cutout blades; 32" x ¾" smooth blades; feathering blade with scraper for rear gang
- › Weight per blade: 379–550 pounds depending on unit
- › Cutting width: 10'4" to 20'4" depending on unit
- › Dual spring stabilizers level unit in changing ground conditions and absorb rough terrain
- › Extra-heavy-duty gang bolt with thread and nut cover assures problem-free work; wrench included
- › 2¾" triple-lip sealed, greaseable ball-type, toggle-mounted Protect-O-Shield® bearings
- › Adjustable gang angle controls how aggressive the cut is
- › DIAL-A-DEPTH assures plowing at desired depth
- › ¾" x 6½" x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2½" x 2½" square tubing; scrapers mount to ¾" x 3" shanks with heavy-duty u-bolts
- › Transporting lockout, safety chains, slow-moving placard, and light kits included
- › 3 different tongue settings for left and right offset positions
- › Dual 15" x 10" wheels with extra heavy-duty 8-bolt hubs and 12½" x 15" 12-ply tires allow for positive depth control and make between-field movement easy; heavy-duty 5" diameter rock-shaft pivots on greaseable pillow block bearings
- › Powder-coated finish for enhanced durability

FEATURES



PRODUCT PERFORMANCE GUARANTEE—Repair, Replace, or Refund: AMCO Guarantees Performance. The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.



Above: Available with impressive 36" x 1/2" blades featuring 2 1/4" gang axles.



Below: Specially designed oversized 5" x 16" x 2 1/2" hydraulic cylinder lifts harrow for transport.



Above: Dual spring stabilizers level unit in changing ground conditions and absorb rough terrain.



Above: Three tongue settings enable left and right offset positions.



Above: Extreme-duty 5/8" x 3" shanks.



Above: 2 3/4" round-bore greaseable bearings with AMCO's standard 2-year warranty.



MANUFACTURING, INC.

800 S. Industrial Parkway
P. O. Box 1107
Yazoo City, MS 39194

Toll free: 800-748-9022
662-746-4464
Fax: 662-746-6825

Web: www.amcomfg.com
Facebook: www.facebook.com/AMCOManufacturingInc
Email: sales@amcomfg.com

G2 Wheel Offset Harrow Models

Model	Cutting Width	No. of Discs	No. of Bearings	Crawler Approximate Engine HP	Rubber Tired Approximate Engine HP	Approximate Weight lbs*
G2-2032	10'4"	20	8	135-162	202-243	10,179
G2-2432	12'4"	24	12	149-176	216-264	11,767
G2-2832	14'4"	28	12	162-203	243-304	12,508
G2-3232	16'4"	32	16	189-236	284-365	14,113
G2-3632	18'4"	36	16	216-270	324-405	14,821

**Weights shown for models with 32" blades. Add 50 lbs. per blade for models with 36" blades. Specifications for all models subject to change without notice.*



**TOUGH
TILLAGE
TOOLS**