



Selling Points - AMCO G2 *Wheel Offset Harrow* Heavy Primary Tillage



G2 features:

- 8"x6"x1/2" all welded main frame. 60" wide.
- 8"x6"x1/2" gang frames
- Dual 12.5L, 12 ply tires mounted on 15x10" wheels with HD 8-bolt hubs
- Heavy-duty 5" diameter rock-shaft pivots on greasable pillow block bearings
- Adjustable gang angle 20° to 27° front to rear
- Standard 32"x3/8" Cutout blades with 14"x3/16" backup blades behind each blade
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 2 1/4" round axles
- 12 1/2" blade spacing
- 2 3/4" bore, triple-lip sealed, greasable ball-type, toggle-mounted Protect-O-Shield bearings
- AMCO **Protect-O-Shield® bearings** feature an exclusive protective shield to protect its triple seals. Our bearing prevents blown seals and prevents wrap damage.
- AMCO **Protect-O-Shield® bearings** are guaranteed for 2 full years.
- Dual leveling springs compensate automatically on changing ground conditions.
- Three tongue position adjustments for both left and right offset positions.
- 92" long tongue with tongue jack and base hitch clevis
- Standard light kit, safety chains, & SMV emblem

- 5"x16"x2½" hydraulic cylinder with special clevis. Includes hose bundle to tractor.
- Standard fabricated steel bearing risers with wear guards and zerker guards
- Heavy-duty moldboard type scrapers with 5/8"x3" shanks

AMCO Exclusive Product Performance Guarantee – Repair, Replace, or Refund: AMCO Guarantees Performance – The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

Optional Equipment:

- Feathering blade with scraper for rear gang
- Optional blade sizes available
 - 32"x3/8" Plain blades
 - 36"x1/2" Cutout blades

G2 Wheel Offset Harrow Models

Model	Cutting Width	No. of Discs	No. of Bearings	Crawler Approximate Engine HP	Rubber-Tired Approximate Engine HP Required	Approximate Weight lbs*
G2-2032	10'4"	20	8	135-162	202-243	10,179
G2-2432	12'4"	24	12	149-176	216-264	11,767
G2-2832	14'4"	28	12	162-203	243-304	12,508
G2-3232	16'4"	32	16	189-236	284-365	14,113
G2-3632	18'4"	36	16	216-270	324-405	14,821

**Weights shown for models with 32" blades. Add 50 lbs. per blade for models with 36" blades. Specifications for all models subject to change without notice.*

Maintenance Tip:

Gang Bearings – The AMCO G2 offset harrow is equipped with triple lip seal regreasable ball bearings. These bearings are packed and greased at the factory. They should be regreased every week or after each 50 hours of operation. Grease the bearings at the end of each season and at the start of each season. Then raise the harrow and spin the gangs slowly so that grease wraps around the bearing seals. This will protect the seals against the elements while the harrow is not in use.

Apply with low pressure, low volume hand grease gun. Use a good No. 2 gun grease (Lithium Base)