

AMCO

MANUFACTURING, INC.

A-frame hitch accepts category I, II, and III hitches and is quick-hitch compatible

Legs can be set narrow or widened to follow tractor tires



Blades have adjustable cutting angle with 3 settings

WATER FURROW PLOW

AMCO's fast, economical solution for wet fields.

Don't let wet fields cost you precious time during planting and harvest. Standing water in your fields prevents you from planting in a timely manner and can lead to yield-robbing delays.

Designed with blades instead of cutter heads, AMCO's WFP Water Furrow Plow flips dirt aside so water can drain away from your crops. It offers the performance of a PTO-driven ditcher at a more economical price point, ideal for less frequent use.

The 4" x 7" toolbar is available in 110" and 180" cutting widths. Both feature adjustable legs, offering flexibility to set the blades to track behind either dual or single tires. This ensures the drainage ditches are dug into the wheels ruts, deepening them, so no secondary tire ruts trap water in your fields. You can also move the legs in for narrower ditch spacing if preferred.

FEATURES

- A rigid heavy-duty design with 1½" square gangs
- 2 fabricated long gang frame shanks
- 1½" square axles
- Standard parking stands
- Greasable 1½" square Protect-O-Shield® bearings with two-year warranty
- Standard 22" x ¼" smooth/plain disc blades*

**24" x ¼" smooth/plain disc blades are optional*



**TOUGH
TILLAGE
TOOLS**

800 S. Industrial Parkway
P. O. Box 1107
Yazoo City, MS 39194

Toll free: 800-748-9022
662-746-4464

Fax: 662-746-6825

Web: www.amcomfg.com
Facebook: www.facebook.com/AMCOManufacturingInc
Email: sales@amcomfg.com

Model	Toolbar Width	Cutting Width	No. of Disc Blades	Disc Blade Size/ Type	Approx. Engine HP Required	Approx. Weight lbs
WFP110	110"	Adjustable within 110"	2	22" x ¼" smooth/plain	41-81	626
WFP180	180"	Adjustable within 180"	2	22" x ¼" smooth/plain	41-81	730

Specifications subject to change without notice.