

# WHEEL OFFSET HARROWS

1

## MODEL "D41"

9" Spacing

### STANDARD SPECIFICATIONS

**AXLES:** 1-1/8" square, high carbon cold finished steel  
**BLADES:** 22" x 6 Ga. Plain with diminishing leveling blades  
**SCRAPER:** High carbon steel blades on 1/2" x 1-1/2" shanks, mounted on 2 x 2 angle iron

**TONGUE:** Adjustable  
**GANG ANGLE:** 17° to 23° front and rear  
**BEARINGS:** Regreaseable triple sealed gang bearings  
**WHEELS:** Two 14" - 6 hole  
**TRANSPORT WIDTH:** Cutting width plus 6"  
**HYDRAULIC CYLINDERS:** 3 x 8 with stroke control. Includes hose bundle to tractor and hose holder

| MODEL NO.             | Cutting Width                                                     | No. of Discs | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|-----------------------|-------------------------------------------------------------------|--------------|-----------------|---------------------------------|-----------------------------|--------------------|
| D41-1622              | 6'0"                                                              | 16           | 6               | 25 -40                          | 1813 (824)                  | \$ 4,213.00        |
| D41-1822              | 6'9"                                                              | 18           | 6               | 30 -45                          | 1898 (863)                  | 4,390.00           |
| D41-2022              | 7'6"                                                              | 20           | 6               | 35 -50                          | 2048 (931)                  | 4,572.00           |
| D41-2222              | 8'3"                                                              | 22           | 6               | 45 -60                          | 2198 (999)                  | 4,760.00           |
| D41-2422              | 9'0"                                                              | 24           | 8               | 55 -70                          | 2348 (1067)                 | 5,210.00           |
| D41-2622              | 9'9"                                                              | 26           | 8               | 60 -75                          | 2498 (1135)                 | 5,660.00           |
| OPTIONAL EQUIPMENT    |                                                                   |              |                 |                                 |                             |                    |
| BH-20-0001            | Tongue Jack .....                                                 |              |                 |                                 | Add 12 (5.4)                | Add 56.90          |
| AB-01-0005            | Ratchet Jack .....                                                |              |                 |                                 | Add 14 (6.4)                | Add 68.80          |
| AB-01-0006            | Feathering Blade .....                                            |              |                 |                                 | Add 28 (12.7)               | Add 139.60         |
|                       | 20" x 6 Ga. cutout blades in lieu of 22" x 3/16" plain .....      |              |                 |                                 | Ded 3.6 (1.6) ea            | Ded 4.30 ea        |
|                       | 20" x 6 Ga. plain blades in lieu of 22" x 3/16" plain .....       |              |                 |                                 | Ded 2.7 (1.2) ea            | Ded 4.35 ea        |
|                       | 22" x 6 Ga. cutout blades in lieu of 22" x 3/16" plain .....      |              |                 |                                 | Ded -0- ea                  | Ded -0- ea         |
|                       | 22" x 1/4" (6mm) cutout blades in lieu of 22" x 3/16" plain ..... |              |                 |                                 | Add 6.7 (3.0) ea            | Add 8.55 ea        |
|                       | 22" x 1/4" (6mm) plain blades in lieu of 22" x 3/16" plain .....  |              |                 |                                 | Add 8.6 (3.9) ea            | Add 10.15 ea       |
| RECOMMENDED TIRE SIZE |                                                                   |              |                 |                                 |                             |                    |
|                       | 9.5L x 14 8-ply Tubeless Tire .....                               |              |                 |                                 | Add 27 (12.3)               | PRICE UPON REQUEST |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**MANUFACTURING, INC.**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

# WHEEL OFFSET HARROWS

## MODEL "F41"

9" Spacing

(General Purpose)

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

**AXLES:** 1-1/2" (38mm) square, high carbon cold rolled steel

**BLADES:** 22" x 1/4" cutout with back up disc behind right front blade.

**SCRAPER:** Heavy duty high carbon steel blades on 1/2" x 1-1/2" (12.7mm x 38mm) shanks mounted on 2" x 2" x 3/8" (51mm x 51mm x 10mm) angle iron scraper bars.

**TONGUE:** Adjustable, with tongue jack

**GANG ANGLE:** 17° to 23° front and rear

**HYDRAULIC CYLINDERS:** 4 x 8 Hydraulic Cylinder (3000PSI)  
Includes hose bundle to tractor

**BEARINGS:** Protect-O Shield®, heavy duty 1-1/2" (38mm) square bore greasable ball type, toggle mounted, with zerk guards and wear guards

**SPACING:** 9 Inches (229 mm)

**WHEELS:** Two 15 x 6 with 6 bolt hubs

**WRENCHES:** One for gang bolts

**WEIGHT:** 108 to 134 lbs. per blade (49 to 61 kg. per blade). 288 to 357 lbs. per foot (429 to 531 kg. per meter).

**TRANSPORT WIDTH:** Cutting with plus 6" (2m) plus additional 10" (0.3m) with feathering blades.

| MODEL NO.             | Cutting Width                                            | No. of Discs | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|-----------------------|----------------------------------------------------------|--------------|-----------------|---------------------------------|-----------------------------|--------------------|
| F41-1822              | 6'9" (2.06m)                                             | 18           | 6               | 50-65 (37-48)                   | 2374 (1079)                 | \$ 5,877.00        |
| F41-2022              | 7'6" (2.29m)                                             | 20           | 6               | 55-70 (41-52)                   | 2514 (1143)                 | 6,073.00           |
| F41-2222              | 8'3" (2.51m)                                             | 22           | 8               | 60-75 (45-56)                   | 2747 (1249)                 | 6,784.00           |
| F41-2422              | 9'0" (2.74m)                                             | 24           | 8               | 65-80 (48-60)                   | 2868 (1304)                 | 7,006.00           |
| F41-2622              | 9'9" (3.00m)                                             | 26           | 8               | 70-85 (52-63)                   | 2982 (1355)                 | 7,156.00           |
| F41-2822              | 10'6" (3.20m)                                            | 28           | 8               | 75-90 (56-67)                   | 3203 (1456)                 | 7,370.00           |
| OPTIONAL EQUIPMENT    |                                                          |              |                 |                                 |                             | +                  |
| AB-01-0002            | Feathering blade with scraper for rear gang .....        |              |                 |                                 | Add 26 (12)                 | Add 158.10         |
|                       | 22" x 6 Ga. plain blades in lieu of standard .....       |              |                 |                                 | Ded 6.7 (3.0) ea            | Ded 7.00 ea        |
|                       | 22" x 6 Ga. cutout blades in lieu of standard .....      |              |                 |                                 | Ded 7.1 (3.2) ea            | Ded 8.00 ea        |
|                       | 22" x 1/4" (6mm) plain blades in lieu of standard .....  |              |                 |                                 | Add 1.9 (.9) ea             | Add 1.60 ea        |
|                       | 24" x 1/4" (6mm) cutout blades in lieu of standard ..... |              |                 |                                 | Add 6.9 (3.1) ea            | Add 9.25 ea        |
|                       | 24" x 1/4" (6mm) plain blades in lieu of standard .....  |              |                 |                                 | Add 8.6 (3.9) ea            | Add 8.75 ea        |
| RECOMMENDED TIRE SIZE |                                                          |              |                 |                                 |                             |                    |
|                       | 6.70 x 15 or 9.5L x 15 Tires, 6 or 8 Ply .....           |              |                 |                                 | Add 27 (12.3)               | PRICE UPON REQUEST |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

MANUFACTURING, INC.



# WHEEL OFFSET HARROWS

## MODEL "J41"

10-1/2" Spacing

(General Purpose)

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                             |                                                                                                                                                                                         |                         |                                                                                                                               |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>               | 1-1/2" (38mm) square, high carbon cold rolled steel                                                                                                                                     | <b>BEARINGS:</b>        | Protect-O Shield®, heavy duty 1-1/2" (38mm) square bore greasable ball type, toggle mounted, with zerk guards and wear guards |
| <b>BLADES:</b>              | 24" x 1/4" cutout with back up disc behind right front blade.                                                                                                                           | <b>SPACING:</b>         | 10-1/2 Inches (267mm)                                                                                                         |
| <b>SCRAPER:</b>             | Spring steel scraper with a 3/8" x 2" heat treated spring steel shank and a 3/16" x 6-1/2" x 8" replaceable high carbon steel scraper blade. Scraper bars are 3" x 2" x 3/8" angle iron | <b>WHEELS:</b>          | Two 15 x 6 with 6 bolt hubs                                                                                                   |
| <b>TONGUE:</b>              | Adjustable, with tongue jack                                                                                                                                                            | <b>WRENCHES:</b>        | One for gang bolts                                                                                                            |
| <b>GANG ANGLE:</b>          | 17° to 23° front and rear                                                                                                                                                               | <b>WEIGHT:</b>          | 124 to 155 lbs. per blade (56 to 70 kg. per blade). 287 to 354 lbs. per foot (427 to 527 kg. per meter)                       |
| <b>HYDRAULIC CYLINDERS:</b> | 4 x 8 Hydraulic Cylinder (3000PSI). Includes hose bundle to tractor.                                                                                                                    | <b>TRANSPORT WIDTH:</b> | Cutting width plus 6" (2mm) plus additional 10" (0.3mm) with feathering blades                                                |

| MODEL NO.             | Cutting Width                                            | No. of Discs | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price  |
|-----------------------|----------------------------------------------------------|--------------|-----------------|---------------------------------|-----------------------------|---------------------|
| J41-1624              | 7'0" (2.13m)                                             | 16           | 6               | 50-65 (37-48)                   | 2538 (1154)                 | \$ 6,110.00         |
| J41-1824              | 7'10" (2.39m)                                            | 18           | 6               | 55-70 (41-52)                   | 2685 (1220)                 | 6,371.00            |
| J41-2024              | 8'8" (2.64m)                                             | 20           | 6               | 60-75 (45-56)                   | 2851 (1296)                 | <u>6,663.00</u>     |
| J41-2224              | 9'6" (2.90m)                                             | 22           | 8               | 65-80 (48-60)                   | <u>3100</u> (1409)          | <u>7,381.00</u>     |
| J41-2424              | 10'4" (3.15m)                                            | 24           | 8               | 70-85 (52-63)                   | 3291 (1496)                 | 7,612.00            |
| OPTIONAL EQUIPMENT    |                                                          |              |                 |                                 |                             |                     |
| AB-01-0003            | Feathering blade with scraper for rear gangs .....       |              |                 |                                 | Add 28 (13)                 | Add 165.50          |
|                       | 24" x 1/4" (6mm) plain blades in lieu of standard .....  |              |                 |                                 | Add 2.0 (.9) ea             | Ded 1.00 ea         |
|                       | 26" x 1/4" (6mm) cutout blades in lieu of standard ..... |              |                 |                                 | Add 3.4 (1.6) ea            | Add <u>11.50 ea</u> |
|                       | 26" x 1/4" (6mm) plain blades in lieu of standard .....  |              |                 |                                 | Add 8.6 (3.9) ea            | Add 7.50 ea         |
| RECOMMENDED TIRE SIZE |                                                          |              |                 |                                 |                             |                     |
|                       | 6.70 x 15 or 9.5L x 15 Tires, 6 or 8 Ply .....           |              |                 |                                 | Add 27 (12.3)               | PRICE UPON REQUEST  |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**MANUFACTURING, INC.**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

# WHEEL OFFSET HARROWS

## MODEL "F41-B"

9" Spacing

(Rocky and Woody Conditions)

### STANDARD SPECIFICATIONS

(Metric in Parentheses)

|                             |                                                                                                                                                                                        |                         |                                                                                                                               |
|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>               | 1-1/2" (38mm) square, high carbon cold rolled steel                                                                                                                                    | <b>BEARINGS:</b>        | Protect-O Shield®, heavy duty 1-1/2" (38mm) square bore greasable ball type, toggle mounted with zerkl guards and wear guards |
| <b>BLADES:</b>              | 24" x 1/4" square blades with back up disc behind right front blade                                                                                                                    | <b>SPACING:</b>         | 9 Inches (229mm)                                                                                                              |
| <b>SCRAPER:</b>             | Spring steel scraper with a 3/8" x 2" heat treated spring steel shank and 3/16" x 6-1/2" x 8" replaceable high carbon steel scraper blade. Scraper bars are 3" x 2" x 3/8" angle iron. | <b>WHEELS:</b>          | Two 15 x 6 with 6 bolt hubs                                                                                                   |
| <b>TONGUE:</b>              | Adjustable with tongue jack                                                                                                                                                            | <b>WRENCHES:</b>        | One for gang bolts                                                                                                            |
| <b>GANG ANGLE:</b>          | 17° to 23° front and rear                                                                                                                                                              | <b>WEIGHT:</b>          | 130 - 153 lbs. per blade 348 - 408 lbs per foot                                                                               |
| <b>HYDRAULIC CYLINDERS:</b> | 4 x 8 Hydraulic Cylinders (3000PSI) Includes hose bundle to tractor                                                                                                                    | <b>BEARING RISER:</b>   | Spring steel shock absorber shank, 1/14" x 2" (32mm x 51.2mm)                                                                 |
|                             |                                                                                                                                                                                        | <b>TRANSPORT WIDTH:</b> | Width of cut plus 6" plus additional 10" with feathering blade                                                                |

| MODEL NO.             | Cutting Width                                      | No. of Discs | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|-----------------------|----------------------------------------------------|--------------|-----------------|---------------------------------|-----------------------------|--------------------|
| F41B-1824             | 6'9" (2.06m)                                       | 18           | 8               | 50 - 65 (37-48)                 | 2753 (1251)                 | \$ 6,843.00        |
| F41B-2024             | 7'6" (2.29m)                                       | 20           | 8               | 55-70 (41-52)                   | 2902 (1319)                 | 6,976.00           |
| F41B-2224             | 8'3" (2.51m)                                       | 22           | 8               | 60-75 (45-56)                   | 2998 (1363)                 | 7,355.00           |
| F41B-2424             | 9'0" (2.74m)                                       | 24           | 8               | 65-80 (48-60)                   | 3128 (1427)                 | 7,736.00           |
| OPTIONAL EQUIPMENT    |                                                    |              |                 |                                 |                             |                    |
| AB-01-0003            | Feathering blade with scraper for rear gangs ..... |              |                 |                                 | Add 28 (13)                 | Add 165.50         |
| RECOMMENDED TIRE SIZE |                                                    |              |                 |                                 |                             |                    |
|                       | 6.70 x 15 or 9.5L x 15 Tires, 6 or 8 Ply .....     |              |                 |                                 | Add 27 (12.3)               | PRICE UPON REQUEST |

AMCO P1. Effective March 15, 2004

P.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**MANUFACTURING, INC.**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

# WHEEL OFFSET HARROWS

## MODEL "J41-B"

10-1/2" Spacing

(Rocky and Woody Conditions)

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                            |                                                                                                                                                                                        |                         |                                                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>              | 1-1/2" (38mm) square, high carbon cold rolled steel                                                                                                                                    | <b>BEARINGS:</b>        | Protect-O Shield®, heavy duty 1-1/2" (38mm) square bore greasable ball type toggle mounted with zerkl guards and wear guards |
| <b>BLADES:</b>             | 24" x 1/4" square blades with back up disc behind right front blade                                                                                                                    | <b>SPACING:</b>         | 10-1/2 Inches (267mm)                                                                                                        |
| <b>SCRAPER:</b>            | Spring steel scraper with a 3/8" x 2" heat treated spring steel shank and 3/16" x 6-1/2" x 8" replaceable high carbon steel scraper blade. Scraper bars are 3" x 2" x 3/8" angle iron. | <b>WHEELS:</b>          | Two 15 x 6 with 6 bolt hubs                                                                                                  |
| <b>TONGUE:</b>             | Adjustable with tongue jack                                                                                                                                                            | <b>WRENCHES:</b>        | One for gang bolts                                                                                                           |
| <b>GANG ANGLE:</b>         | 17° to 23° front and rear                                                                                                                                                              | <b>WEIGHT:</b>          | 140 - 177 lbs. per blade; 340 - 371 lbs. per foot                                                                            |
| <b>HYDRAULIC CYLINDER:</b> | 4 x 8 Hydraulic Cylinder (3000 PSI) Includes hose bundle to tractor.                                                                                                                   | <b>BEARING RISER:</b>   | Spring Steel shock absorber shank, 1-1/4" x 2" (32mm x 51.2mm)                                                               |
|                            |                                                                                                                                                                                        | <b>TRANSPORT WIDTH:</b> | Width of cut plus 6" plus additional 10" with feathering blade.                                                              |

| MODEL NO.             | Cutting Width                                      | No. of Discs | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|-----------------------|----------------------------------------------------|--------------|-----------------|---------------------------------|-----------------------------|--------------------|
| J41B-1624             | 7'0" (2.13m)                                       | 16           | 8               | 50-65 (37-48)                   | 2827 (1285)                 | \$ 6,930.00        |
| J41B-1824             | 7'10" (2.39m)                                      | 18           | 8               | 55-70 (41-52)                   | 2973 (1351)                 | 7,197.00           |
| J41B-2024             | 8'8" (2.64m)                                       | 20           | 8               | 60-75 (45-56)                   | 3137 (1426)                 | 7,508.00           |
| J41B-2224             | 9'6" (2.90m)                                       | 22           | 8               | 65-80 (48-60)                   | 3232 (1469)                 | 7,762.00           |
| J41B-2424             | 10'4" (3.15m)                                      | 24           | 8               | 70-85 (52-63)                   | 3362 (1528)                 | 8,072.00           |
| OPTIONAL EQUIPMENT    |                                                    |              |                 |                                 |                             |                    |
| AB-01-0003            | Feathering blade with scraper for rear gangs ..... |              |                 |                                 | Add 28 (13)                 | Add \$165.50       |
| RECOMMENDED TIRE SIZE |                                                    |              |                 |                                 |                             |                    |
|                       | 6.70 X 15 or 9.52 X 15 Tires, 6 or 8 Ply .....     |              |                 |                                 | Add 27 (12.3)               | PRICE UPON REQUEST |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# WHEEL OFFSET HARROWS

## MODEL "F42"(HEAVY DUTY)

9" Spacing

(Primary Tillage)

### STANDARD SPECIFICATIONS

|                       |                                                                                                                                       |                             |                                                                                                                                                         |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>         | 1-1/2" (38mm) square, high carbon cold rolled steel                                                                                   | <b>BEARINGS:</b>            | Protect-O Shield®, heavy duty 1-1/2" (38mm) square bore greasable ball type, toggle mounted, with zerk guards and wear guards.                          |
| <b>BLADES:</b>        | 24" x 1/4" (6mm) Plain with diminishing leveling blades. Back up discs behind right front blade.                                      | <b>SPACING:</b>             | 9 Inches (229mm)                                                                                                                                        |
| <b>SCRAPER:</b>       | Heavy duty high carbon steel blades on 3/8" x 2" (10mm x 51mm) spring steel shanks, mounted on 3" x 2" x 3/8" angle iron scraper bar. | <b>WRENCHES:</b>            | 2 for gang bolts                                                                                                                                        |
| <b>TONGUE:</b>        | Adjustable, 88-1/2" (2.25m) long with tongue jack and reversible ductile iron clevis.                                                 | <b>WEIGHT:</b>              | 164 to 197 lbs. per blade (74 to 89 kg. per blade, 439 to 525 lbs. per foot (653 to 781 kg. per meter)                                                  |
| <b>GANG ANGLE:</b>    | 17° to 25° front and rear.                                                                                                            | <b>TRANSPORT WIDTH:</b>     | Cutting width plus 12" (0.30m) plus additional 12" (0.30m) with feathering blades                                                                       |
| <b>BEARING RISER:</b> | Fabricated steel, 16-3/4" high.                                                                                                       | <b>HYDRAULIC CYLINDERS:</b> | 4" x 8" x 1-1/2" with stroke control on 50" (1.27m) main frame, 4" x 16" x 2" on 86" (2.18m) main frame (3000PSI each). Includes hose bundle to tractor |
| <b>WHEELS:</b>        | Dual 15 x 8 with 6 bolt hubs = 30.00                                                                                                  |                             |                                                                                                                                                         |

| MODEL NO.                                                                                | Cutting Width                                                                                              | No. of Discs | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|--------------|-----------------|---------------------------------|-----------------------------|--------------------|
| <b>50" (1.27m) MAIN FRAME</b>                                                            |                                                                                                            |              |                 |                                 |                             |                    |
| F42-2224                                                                                 | 8'3" (2.51m)                                                                                               | 22           | 8               | 70-90 (52-67)                   | 4038 (1835)                 | \$ 10,140.00       |
| F42-2424                                                                                 | 9'0" (2.74m)                                                                                               | 24           | 8               | 80-105 (60-78)                  | 4182 (1901)                 | 10,423.00          |
| F42-2824                                                                                 | 10'6" (3.20m)                                                                                              | 28           | 8               | 90-120 (67-89)                  | 4677 (2126)                 | 11,463.00          |
| F42-3224                                                                                 | 12'0" (3.66m)                                                                                              | 32           | 10              | 100-140 (75-104)                | 5115 (2325)                 | 12,207.00          |
| <b>85" (2.18m) MAIN FRAME</b>                                                            |                                                                                                            |              |                 |                                 |                             |                    |
| F42B-3224                                                                                | 12'0" (3.66m)                                                                                              | 32           | 10              | 110-150 (82-112)                | 6316 (2871)                 | 13,977.00          |
| F42-3624                                                                                 | 13'6" (4.11m)                                                                                              | 36           | 12              | 120-160 (89-119)                | 6600 (3000)                 | 14,945.00          |
| F42-4024                                                                                 | 15'0" (4.57m)                                                                                              | 40           | 12              | 135-175 (101-130)               | 6900 (3136)                 | 15,697.00          |
| F42-4424*                                                                                | 16'6" (5.03m)                                                                                              | 44           | 14              | 150-190 (112-142)               | 7917 (3599)                 | 17,863.00          |
| F42-4824*                                                                                | 17'6" (5.3m)                                                                                               | 48           | 16              | 160-200 (120-150)               | 8201 (3728)                 | 19,141.00          |
| <b>*Equipped with auxiliary frames and clamps and 8 hole hubs in lieu of Std. 6 hole</b> |                                                                                                            |              |                 |                                 |                             |                    |
| <b>OPTIONAL EQUIPMENT</b>                                                                |                                                                                                            |              |                 |                                 |                             |                    |
| AB-01-0003                                                                               | Feathering blade with scraper for rear gang.....                                                           |              |                 |                                 | Add 31 (14)                 | Add 162.80         |
| AN-20-0001                                                                               | 15 x 10" wheels in lieu of 15" x 8" wheels .....                                                           |              |                 |                                 | Add 6 (2.7) ea              | Add 8.80 ea        |
|                                                                                          | 24" x 1/4" (6mm) cutout blades in lieu of standard... ..                                                   |              |                 |                                 | Ded 2.0 (0.9) ea            | Add 1.00 ea        |
|                                                                                          | Shock absorber bearing riser with 1-1/4" x 2-1/2" (32mm x 64mm) spring steel shank - Add per bearing ..... |              |                 |                                 | Add 21 (9.5) ea             | Add 46.31 ea       |
| <b>RECOMMENDED TIRE SIZE</b>                                                             |                                                                                                            |              |                 |                                 |                             |                    |
|                                                                                          | 9.5L x 15 Tires, 6 or 8 Ply, on 15 x 8 Wheels .....                                                        |              |                 |                                 | Add 27 (12.3)               | PRICE UPON REQUEST |
|                                                                                          | 11L x 15 Tires, 6 or 8 Ply, on 15 x 10 Wheels .....                                                        |              |                 |                                 | Add 35 (15.9)               |                    |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**MANUFACTURING, INC.**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# WHEEL OFFSET HARROWS

## MODEL "J42"(HEAVY DUTY)

10-1/2" Spacing

(Primary Tillage)

### STANDARD SPECIFICATIONS

|                       |                                                                                                                                       |                             |                                                                                                                                                          |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>         | 1-1/2" (38mm) square, high carbon cold rolled steel                                                                                   | <b>BEARINGS:</b>            | Protect-O Shield®, heavy duty 1-1/2" (38mm) square bore greasable ball type, toggle mounted, with zerk guards and wear guards.                           |
| <b>BLADES:</b>        | 24" x 1/4" (6mm) plain with diminishing leveling blades. Back up disc behind right front blade.                                       | <b>SPACING:</b>             | 10-1/2 Inches (267mm)                                                                                                                                    |
| <b>SCRAPER:</b>       | Heavy duty high carbon steel blades on 3/8" x 2" (10mm x 51mm) spring steel shanks, mounted on 3" x 2" x 3/8" angle iron scraper bar. | <b>WHEELS:</b>              | Dual 15 x 8 with 6 bolt hubs                                                                                                                             |
| <b>TONGUE:</b>        | Adjustable, 88-1/2" (2.25m) long with tongue jack and reversible ductile iron clevis                                                  | <b>WRENCHES:</b>            | 2 for gang bolts                                                                                                                                         |
| <b>GANG ANGLE:</b>    | 17° to 25° front to rear                                                                                                              | <b>WEIGHT:</b>              | 179 to 208 lbs. per blade (81 to 94 kg. per blade) 422 to 480 lbs per foot (628 to 714 kg. per meter)                                                    |
| <b>BEARING RISER:</b> | Fabricated steel, 16-3/4" high                                                                                                        | <b>TRANSPORT WIDTH:</b>     | Cutting width plus 12" (0.30m) plus additional 12" (0.30m) with feathering blades                                                                        |
|                       |                                                                                                                                       | <b>HYDRAULIC CYLINDERS:</b> | 4" x 8" x 1-1/2" with stroke control on 50" (1.27m) main frame, 4" x 16" x 2" on 86" (2.18m) main frame (each 3000PSI), Includes hose bundle to tractor. |

| MODEL NO.                                                                        | Cutting Width                                                                                | No. of Discs           | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|------------------------|-----------------|---------------------------------|-----------------------------|--------------------|
|                                                                                  |                                                                                              | 50" (1.27m) MAIN FRAME |                 |                                 |                             |                    |
| J42-2024                                                                         | 8'8" (2.64m)                                                                                 | 20                     | 6               | 75-95 (56-71)                   | 3829 (1740)                 | \$ 9,464.00        |
| J42-2424                                                                         | 10'4" (3.15m)                                                                                | 24                     | 8               | 90-120 (67-89)                  | 4506 (2048)                 | 10,830.00          |
| J42-2824                                                                         | 12'0" (3.66m)                                                                                | 28                     | 10              | 100-130 (75-97)                 | 4929 (2240)                 | 11,749.00          |
|                                                                                  |                                                                                              | 86" (2.18m) MAIN FRAME |                 |                                 |                             |                    |
| J42B-2824                                                                        | 12'0" (3.66m)                                                                                | 28                     | 10              | 110-140 (82-104)                | 5955 (2707)                 | 13,697.00          |
| J42-3224                                                                         | 13'8" (4.17m)                                                                                | 32                     | 12              | 125-150 (93-112)                | 6450 (2932)                 | 14,428.00          |
| J42-3624                                                                         | 15'4" (4.67m)                                                                                | 36                     | 12              | 140-175 (104-130)               | 6802 (3092)                 | 15,114.00          |
| J42-4024*                                                                        | 17'0" (5.18m)                                                                                | 40                     | 12              | 160-190 (119-142)               | 7663 (3483)                 | 16,705.00          |
| J42-4424*                                                                        | 18'8" (5.69m)                                                                                | 44                     | 16              | 175-205 (130-153)               | 8249 (3750)                 | 18,179.00          |
| J42-4824*                                                                        | 20'6" (6.25m)                                                                                | 48                     | 16              | 190-220 (142-164)               | 8601 (3910)                 | 19,624.00          |
| *Equipped with auxiliary frames and clamps and 8 hole hub in lieu of Std. 6 hole |                                                                                              |                        |                 |                                 |                             |                    |
| OPTIONAL EQUIPMENT                                                               |                                                                                              |                        |                 |                                 |                             |                    |
| AB-01-0003                                                                       | Feathering blade with scraper for rear gang.....                                             |                        |                 |                                 | Add 31 (14)                 | Add 165.50         |
| AN-20-0001                                                                       | 15" x 10" wheels in lieu of 15" x 8" wheels .....                                            |                        |                 |                                 | Add 6 (2.7) ea              | Add 8.80 ea        |
|                                                                                  | 24" x 1/4" (6mm) cutout blades in lieu of standard .....                                     |                        |                 |                                 | Ded 2.0 (0.9) ea            | Add 1.00 ea        |
|                                                                                  | 26" x 1/4" (6mm) plain blades in lieu of standard .....                                      |                        |                 |                                 | Add 5.8 (2.6) ea            | Add 8.25 ea        |
|                                                                                  | 26" x 1/4" (6mm) cutout blades in lieu of standard .....                                     |                        |                 |                                 | Add 3.8 (1.7) ea            | Add 12.00 ea       |
|                                                                                  | Shock Absorber bearing riser with 1-1/4" x 2-1/2" spring steel shank - Add per bearing ..... |                        |                 |                                 | Add 21 (9.5) ea             | Add 46.31 ea       |
| RECOMMENDED TIRE SIZE                                                            |                                                                                              |                        |                 |                                 |                             |                    |
|                                                                                  | 9.5L x 15 Tires, 6 or 8 Ply, on 15 x 8 Wheels .....                                          |                        |                 |                                 | Add 27 (12.3)               | PRICE UPON REQUEST |
|                                                                                  | 11L x 15 Tires, 6 or 8 Ply, on 15 x 10 Wheels .....                                          |                        |                 |                                 | Add 35 (15.9)               |                    |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# WHEEL OFFSET HARROWS

## MODEL "J43" (EXTRA HEAVY DUTY)

10-1/2" Spacing

(Primary Tillage)

### STANDARD SPECIFICATIONS

|                       |                                                                                                                                      |                             |                                                                                                                                                         |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>         | 1-1/2" (38mm) square, high carbon cold rolled steel                                                                                  | <b>BEARINGS:</b>            | Protect-O Shield®, extra heavy duty 2-11/16" (68mm) bore greasable ball type, toggle mounted with zerk guards and wear guards.                          |
| <b>BLADES:</b>        | 24" x 1/4" (6mm) plain with diminishing leveling blades. Back up disc behind right front blade.                                      | <b>SPACING:</b>             | 10-1/2" (267mm)                                                                                                                                         |
| <b>SCRAPER:</b>       | Heavy duty high carbon steel blades on 3/8" x 2" (10mm x 51mm) spring steel shanks, mounted on 3" x 2" x 3/8" angle iron scraper bar | <b>WHEELS:</b>              | Dual 15 x 8 with 6 bolt hubs                                                                                                                            |
| <b>TONGUE:</b>        | Adjustable, 88-1/2" (2.25m) long with tongue jack and reversible ductile iron clevis.                                                | <b>WRENCHES:</b>            | 2 for gang bolts                                                                                                                                        |
| <b>GANG ANGLE:</b>    | 17° to 25° front to rear                                                                                                             | <b>WEIGHT:</b>              | 205 to 231 lbs. per blade (93 to 105 kg. per blade) 483 to 533 lbs per foot ( 719 to 793 kg. per meter)                                                 |
| <b>BEARING RISER:</b> | Spring steel shock absorber shank, 1-1/4" by 2-1/2" (32mm x 64mm)                                                                    | <b>TRANSPORT WIDTH:</b>     | Cutting width plus 12" (0.30m) plus additional 12" (0.30m) with feathering blades.                                                                      |
|                       |                                                                                                                                      | <b>HYDRAULIC CYLINDERS:</b> | 4" x 8" x 1-1/2" with stroke control on 50" (1.27m) main frame, 4" x 16" x 2" on 86" (2.18m) main frame (each 3000 PSI) Includes hose bundle to tractor |

| MODEL NO.                                                                         | Cutting Width                                            | No. of Discs | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|-----------------------------------------------------------------------------------|----------------------------------------------------------|--------------|-----------------|---------------------------------|-----------------------------|--------------------|
| 50" (1.27m) MAIN FRAME                                                            |                                                          |              |                 |                                 |                             |                    |
| J43-2024                                                                          | 8'8" (2.64m)                                             | 20           | 6               | 85-100 (63-75)                  | 4195 (1907)                 | \$ 10,631.00       |
| J43-2424                                                                          | 10'4" (3.15m)                                            | 24           | 8               | 90-120 (6-89)                   | 4928 (2240)                 | 12,214.00          |
| J43-2824                                                                          | 12'0" (3.66m)                                            | 28           | 10              | 110-140 (82-104)                | 5509 (2504)                 | 13,644.00          |
| 86" (2.18m) MAIN FRAME                                                            |                                                          |              |                 |                                 |                             |                    |
| J43B-2824                                                                         | 12'0" (3.66m)                                            | 28           | 10              | 120-150 (89-112)                | 6508 (2958)                 | 14,840.00          |
| J43-3224                                                                          | 13'8" (4.17m)                                            | 32           | 12              | 130-170 (97-127)                | 7105 (3230)                 | 16,582.00          |
| J43-3624*                                                                         | 15'4" (4.67m)                                            | 36           | 12              | 140-180 (104-134)               | 7934 (3629)                 | 18,134.00          |
| J43-4024*                                                                         | 17'0" (5.18m)                                            | 40           | 12              | 160-200 (119-149)               | 8393 (3815)                 | 18,856.00          |
| J43-4424*                                                                         | 18'8" (5.69m)                                            | 44           | 16              | 180-225 (134-168)               | 9143 (4156)                 | 21,222.00          |
| *Equipped with auxiliary frames and clamps and 8 hole hubs in lieu of Std. 6 hole |                                                          |              |                 |                                 |                             |                    |
| OPTIONAL EQUIPMENT                                                                |                                                          |              |                 |                                 |                             |                    |
| AB-01-0003                                                                        | Feathering blade with scraper for rear gang.....         |              |                 |                                 | Add 31 (14)                 | Add 165.50         |
|                                                                                   | LA.SPECIAL: Scrapers and Scraperbars, per blade .....    |              |                 |                                 | Add 2.5 (1.1) ea            | Add 20.35 ea       |
| AN-20-0001                                                                        | 15" x 10" wheels in lieu of 15" x 8" wheels .....        |              |                 |                                 | Add 6 (2.7) ea              | Add 8.80 ea        |
|                                                                                   | 24" x 1/4" (6mm) cutout blades in lieu of standard ..... |              |                 |                                 | Ded 2.0 (0.9)ea             | Add 1.00 ea        |
|                                                                                   | 26" x 1/4" (6mm) plain blades in lieu of standard .....  |              |                 |                                 | Add 5.8 (2.6) ea            | Add 8.25 ea        |
|                                                                                   | 26" x 1/4" (6mm) cutout blades in lieu of standard ..... |              |                 |                                 | Add 3.8 (1.7) ea            | Add 12.00 ea       |
|                                                                                   | 26" x 5/16" plain blades in lieu of standard .....       |              |                 |                                 | Priced Upon Request         |                    |
|                                                                                   | 26" x 5/16" cutout blades in lieu of standard .....      |              |                 |                                 | Priced Upon Request         |                    |
| RECOMMENDED TIRE SIZE                                                             |                                                          |              |                 |                                 |                             |                    |
|                                                                                   | 9.5L x 15 Tires, 8 Ply, on 15 x 8 Wheels .....           |              |                 |                                 | Add 27 (12.3)               | PRICE UPON REQUEST |
|                                                                                   | 11L x 15 Tires, 8 Ply, on 15 x 10 Wheels .....           |              |                 |                                 | Add 35 (15.9)               |                    |
| Note: 6 Ply Tires Permissible on 15'4" and Smaller                                |                                                          |              |                 |                                 |                             |                    |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# WHEEL OFFSET HARROWS

## MODEL "J44" (EXTRA HEAVY DUTY)

10-1/2" Spacing

(Primary Tillage)

### STANDARD SPECIFICATIONS

|                       |                                                                                                                                                                                  |                             |                                                                                                                                                        |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>         | 1-1/2" (38mm) square, high carbon cold rolled steel                                                                                                                              | <b>BEARINGS:</b>            | Protect-O-Shield®, extra heavy duty 2-11/16" (68mm) bore greasable ball type, toggle mounted with zerk guards and wear guards.                         |
| <b>BLADES:</b>        | 24" x 1/4" (6mm) plain with diminishing leveling blades. <u>Back up disc behind each blade.</u>                                                                                  | <b>SPACING:</b>             | 10-1/2" (267mm)                                                                                                                                        |
| <b>SCRAPER:</b>       | Heavy duty high carbon steel blades on 3/8" x 2-1/2" (10mm x 51mm) spring steel shanks, mounted on scraper bars of 2-1/2" x 2-1/2" x 1/4" (64mm x 64mm x 6.4mm) structural tube. | <b>WHEELS:</b>              | Dual 15 x 8 with 6 bolt hubs.                                                                                                                          |
| <b>TONGUE:</b>        | Adjustable, 88-1/2" (2.25m) long with tongue jack and reversible ductile iron clevis.                                                                                            | <b>WEIGHT:</b>              | 210 to 237 lbs. per blade (95 to 108 kg. per blade) 495 to 546 lbs. per foot (737 to 812 kg. per meter)                                                |
| <b>GANG ANGLE:</b>    | 17° to 25° front to rear                                                                                                                                                         | <b>TRANSPORT WIDTH:</b>     | Cutting width plus 12" (0.30m) plus additional 12" (0.30m) with feathering blades.                                                                     |
| <b>BEARING RISER:</b> | Spring steel shock absorber shank, 1-1/4" by 2-1/2" (32mm x 64mm).                                                                                                               | <b>HYDRAULIC CYLINDERS:</b> | 4" x 8" x 1-1/2" with stroke control on 50" (1.27m) main frame, 4" x 16" 2" on 86" (2.18m) main frame (Each 3000 PSI) Includes hose bundle to tractor. |
| <b>WRENCHES:</b>      | 2 for gang bolts                                                                                                                                                                 |                             |                                                                                                                                                        |

| MODEL NO.  | Cutting Width                                            | No. of Discs                                               | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|------------|----------------------------------------------------------|------------------------------------------------------------|-----------------|---------------------------------|-----------------------------|--------------------|
|            |                                                          | <b>50" (1.27m) MAIN FRAME</b>                              |                 |                                 |                             |                    |
| J44-2024   | 8'8" (2.64m)                                             | 20                                                         | 6               | 95-120 (71-90)                  | 4356 (1980)                 | \$ 11,353.00       |
| J44-2424   | 10'4" (3.15m)                                            | 24                                                         | 8               | 110-130 (82-97)                 | 5114 (2325)                 | 12,911.00          |
|            |                                                          | <b>86" (2.18m) MAIN FRAME</b>                              |                 |                                 |                             |                    |
| J44-2824   | 12'0" (3.66m)                                            | 28                                                         | 10              | 120-160 (89-119)                | 6740 (3064)                 | 16,123.00          |
| J44-3224   | 13'8" (4.17m)                                            | 32                                                         | 12              | 130-170 (97-127)                | 7359 (3345)                 | 17,692.00          |
| J44-3624*  | 15'4" (4.67m)                                            | 36                                                         | 12              | 140-180 (104-134)               | 8266 (3757)                 | 19,432.00          |
| J44-4024*  | 17'0" (5.18m)                                            | 40                                                         | 16              | 160-200 (119-149)               | 9081 (4127)                 | 21,723.00          |
| J44-4424*  | 18'8" (5.69m)                                            | 44                                                         | 16              | 180-225 (134-168)               | 9486 (4312)                 | 22,503.00          |
|            |                                                          | *Equipped with auxiliary frames and clamps and 8 hole hubs |                 |                                 |                             |                    |
|            |                                                          | <b>OPTIONAL EQUIPMENT</b>                                  |                 |                                 |                             |                    |
| AC-01-0005 | Feathering blade with scraper for rear gang .....        |                                                            |                 |                                 | Add 26 (12) ea              | Add 205.00         |
| AN-20-0001 | 15" x 10" wheels in lieu of 15" x 8" wheels .....        |                                                            |                 |                                 | Add 6 (2.7) ea              | Add 8.80 ea        |
|            | 24" x 1/4" (6mm) cutout blades in lieu of standard ..... |                                                            |                 |                                 | Ded 2.0 (0.9) ea            | Add 1.00 ea        |
|            | 26" x 1/4" (6mm) plain blades in lieu of standard .....  |                                                            |                 |                                 | Add 5.8 (2.6) ea            | Add 8.25 ea        |
|            | 26" x 1/4" (6mm) cutout blades in lieu of standard ..... |                                                            |                 |                                 | Add 3.8 (1.7) ea            | Add 12.00 ea       |
|            | 26" x 5/16" plain blades in lieu of standard .....       |                                                            |                 |                                 | Priced Upon Request         |                    |
|            | 26" x 5/16" cutout blades in lieu of standard .....      |                                                            |                 |                                 | Priced Upon Request         |                    |
|            |                                                          | <b>RECOMMENDED TIRE SIZE</b>                               |                 |                                 |                             |                    |
|            | 9.5L x 15 Tires, 8 Ply, on 15 x 8 Wheels .....           |                                                            |                 |                                 | Add 21 (12.3)               | PRICE UPON REQUEST |
|            | 11L x 15 Tires, 8 Ply, on 15 x 10 Wheels .....           |                                                            |                 |                                 | Add 35 (19.9)               |                    |
|            | Note: 6 Ply Tires Permissible on 13'8" and Smaller       |                                                            |                 |                                 |                             |                    |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# WHEEL OFFSET HARROWS

## MODEL "R400"(EXTRA HEAVY DUTY)

11-1/2" Spacing

(Primary Tillage)

### STANDARD SPECIFICATIONS

|                       |                                                                                                                                               |                             |                                                                                                                                           |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>         | 1-1/2" square, high carbon cold rolled steel                                                                                                  | <b>BEARINGS:</b>            | Protect-O-Shield®, extra heavy duty                                                                                                       |
| <b>BLADES:</b>        | 28" x 5/16" plain with diminishing leveling blades. Back up disc behind every blade.                                                          |                             | 2-11/16" bore greasable ball type, toggle mounted with zerk guards and wear guards.                                                       |
| <b>SCRAPER:</b>       | Heavy duty high carbon steel blades on 3/8" x 2-1/2" spring steel shanks, mounted on scraper bars of 2-1/2" x 2-1/2" x 1/4" structural steel. | <b>SPACING:</b>             | 11-1/2"                                                                                                                                   |
| <b>TONGUE:</b>        | Adjustable, 88-1/2" long with tongue jack and reversible ductile iron clevis.                                                                 | <b>WHEELS:</b>              | Dual 15 x 8 with 6 bolt hubs                                                                                                              |
| <b>GANG ANGLE:</b>    | 17° to 25° front and rear                                                                                                                     | <b>WEIGHT:</b>              | 220 to 265 lbs per blade                                                                                                                  |
| <b>BEARING RISER:</b> | Fabricated steel                                                                                                                              |                             | 505 to 570 lbs. per foot                                                                                                                  |
| <b>WRENCHES:</b>      | 2 for gang bolts                                                                                                                              | <b>TRANSPORT WIDTH:</b>     | Cutting width plus 12" plus additional 12" with feathering blades.                                                                        |
|                       |                                                                                                                                               | <b>HYDRAULIC CYLINDERS:</b> | 4" x 8" x 1-1/2" with stroke control on 50" main frame, 4" x 16" x 2" on 86" main frame (Each 3000 PSI). Includes hose bundle to tractor. |

| MODEL NO.  | Cutting Width                                                               | No. of Discs                                                                          | No. of Bearings | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|------------|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-----------------|---------------------------------|-----------------------------|--------------------|
|            |                                                                             | <b>50" (1.27m) MAIN FRAME</b>                                                         |                 |                                 |                             |                    |
| R400-1828  | 8'6" (2.59m)                                                                | 18                                                                                    | 6               | 85 - 105 (63 - 79)              | 4436 (2016)                 | \$ 11,442.00       |
| R400-2228  | 10'3" (3.02m)                                                               | 22                                                                                    | 8               | 95 - 120 (71 - 90)              | 5206 (2366)                 | 13,198.00          |
|            |                                                                             | <b>86" (2.18m) MAIN FRAME</b>                                                         |                 |                                 |                             |                    |
| R400-2628  | 12'0" (3.66m)                                                               | 26                                                                                    | 10              | 120 - 145 (90 - 108)            | 6864 (3120)                 | 16,390.00          |
| R400-3028  | 13'9" (4.19m)                                                               | 30                                                                                    | 12              | 130 - 155 (97 - 116)            | 7491 (3405)                 | 17,998.00          |
| R400-3428* | 15'6" (4.72m)                                                               | 34                                                                                    | 12              | 145 - 10 (108 - 127)            | 8413 (3824)                 | 19,872.00          |
| R400-3828* | 17'3" (5.25m)                                                               | 38                                                                                    | 14              | 165 - 195 (123 - 145)           | 9159 (4163)                 | 21,518.00          |
|            |                                                                             | *Equipped with auxiliary frames and clamps and 8 hole hubs in lieu of standard 6 hole |                 |                                 |                             |                    |
|            |                                                                             | <b>OPTIONAL EQUIPMENT</b>                                                             |                 |                                 |                             |                    |
| FA-01-0014 | Safety chain 5/16".....                                                     |                                                                                       |                 |                                 | Priced Upon Request         |                    |
| AF-01-0001 | Feathering blade with scraper for rear gang.....                            |                                                                                       |                 |                                 | Add 42 (19)                 | Add 165.50         |
| AN-20-0001 | 15" x 10" wheels in lieu of 15" x 8" wheels.....                            |                                                                                       |                 |                                 | Add 6 (2.7) ea              | Add 8.80 ea        |
|            | Shock absorber gang risers in lieu of standard gang risers per bearing..... |                                                                                       |                 |                                 | Add 39.8 (18) ea            | Add 60.00 ea       |
|            | 26" x 1/4" (6mm) cutout blades in lieu of standard.....                     |                                                                                       |                 |                                 | Ded 9.3 (4.2) ea            | Ded 20.00 ea       |
|            | 26" x 1/4" (6mm) plain blades in lieu of standard.....                      |                                                                                       |                 |                                 | Ded 7.3 (3.3) ea            | Ded 22.00 ea       |
|            | 28" x 5/16" cutout blades in lieu of standard.....                          |                                                                                       |                 |                                 | Ded 2.0 (0.9) ea            | Add - 0 - ea       |
|            | 26" x 5/16" plain blades in lieu of standard.....                           |                                                                                       |                 |                                 | Ded 7.0 (3.2) ea            | Add 10.25 ea       |
|            | 26" x 5/16" cutout blades in lieu of standard.....                          |                                                                                       |                 |                                 | Ded 8.0 (3.6) ea            | Add 11.00 ea       |
|            | <b>RECOMMENDED TIRE SIZE</b>                                                |                                                                                       |                 |                                 |                             |                    |
|            | 9.5L x 15 Tires, 8 Ply, on 15" x 8" Wheels.....                             |                                                                                       |                 |                                 | Add 27 (12.3)               | PRICE UPON REQUEST |
|            | 11L x 15 Tires, 8 Ply, on 15" x 10" Wheels.....                             |                                                                                       |                 |                                 | Add 35 (15.9)               |                    |
|            | Note: 6 Ply Tires permissible on 13'9" and smaller                          |                                                                                       |                 |                                 |                             |                    |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# WHEEL OFFSET HARROWS

## MODEL "G2"

(Heavy Primary Tillage)

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                    |                                                                             |                             |                                                                                                             |
|--------------------|-----------------------------------------------------------------------------|-----------------------------|-------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>      | 2-1/4" (57mm) round, high carbon cold, rolled steel                         | <b>BEARINGS:</b>            | Protect-O-Shield®, 2-3/4" bore regreasable ball type, toggle mounted                                        |
| <b>BLADES:</b>     | 32" x 3/8" (10mm) cutout with 14" x 3/16" (356 mm x 4.8 mm) back up blades. | <b>SPACING:</b>             | 12-1/2" (318mm)                                                                                             |
| <b>SCRAPER:</b>    | Extra Heavy duty moldboard type with 5/8" x 3" shank                        | <b>WRENCH:</b>              | 1 for gang bolt                                                                                             |
| <b>TONGUE:</b>     | Adjustable, 92" long with tongue jack and reversible ductile iron clevis.   | <b>WEIGHT:</b>              | 379 to 502 lbs. per blade (172 to 228 kg. per blade), 758 to 975 lbs. per foot (1128 to 1451 kg. per meter) |
| <b>GANG ANGLE:</b> | 20° to 27° front to rear                                                    | <b>TRANSPORT WIDTH:</b>     | Width of cut plus 12 inches                                                                                 |
| <b>WHEELS:</b>     | Dual 15 x 10 with extra heavy duty 8 bolt hub                               | <b>HYDRAULIC CYLINDERS:</b> | 5" x 16" x 2-1/2" Hydraulic Cylinder with special clevis and hose bundle to tractor.                        |

| MODEL NO.                                            | Cutting Width                                                                     | No. of Discs | No. of Bearings | Disc Size & Type | Crawler Approximate Drawbar HP Required | Rubber Tired Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|------------------------------------------------------|-----------------------------------------------------------------------------------|--------------|-----------------|------------------|-----------------------------------------|----------------------------------------------|-----------------------------|--------------------|
| TAPERED GANGS                                        |                                                                                   |              |                 |                  |                                         |                                              |                             |                    |
| G2-1632                                              | 8'4" (2.97m)                                                                      | 16           | 8               | 32" Cutout       | 90-110                                  | 150-180                                      | 9507 (4321)                 | \$23,366.00        |
| G2-2032                                              | 10'4" (3.15m)                                                                     | 20           | 8               | 32" Cutout       | 100-120                                 | 150-180                                      | 9991 (4541)                 | 25,165.00          |
| G2-2432                                              | 12'4" (3.76m)                                                                     | 24           | 12              | 32" Cutout       | 110-130                                 | 160-195                                      | 11579 (5263)                | 29,157.00          |
| G2-2832                                              | 14'4" (4.37m)                                                                     | 28           | 12              | 32" Cutout       | 120-150                                 | 180-225                                      | 12320 (5600)                | 31,008.00          |
| G2-3232                                              | 16'4" (4.98m)                                                                     | 32           | 16              | 32" Cutout       | 140-175                                 | 210-270                                      | 13925 (6330)                | 36,289.00          |
| G2-3632                                              | 18'4" (5.59m)                                                                     | 36           | 16              | 32" Cutout       | 160-200                                 | 240-300                                      | 14633 (6651)                | 38,255.00          |
| G2-4032                                              | 20'4" (6.20m)                                                                     | 40           | 16              | 32" Cutout       | 200-240                                 | 280-320                                      | 16153 (7342)                | 39,240.00          |
| Note: Auxiliary Bar Standard Equipment on 20'4" Unit |                                                                                   |              |                 |                  |                                         |                                              |                             |                    |
| RECOMMENDED EQUIPMENT                                |                                                                                   |              |                 |                  |                                         |                                              |                             |                    |
| OPTIONAL EQUIPMENT                                   |                                                                                   |              |                 |                  |                                         |                                              |                             |                    |
| JA-01-0026                                           | Feathering Blade with scraper.....                                                |              |                 |                  |                                         |                                              | 110(50)                     | 263.00             |
|                                                      | 32" x 3/8" (10mm) Plain blades in lieu of standard 32" x 3/8" (10mm) cutout ..... |              |                 |                  |                                         |                                              | Add 35 (16) ea              | Ded 1.25 ea        |
| FA-01-0014                                           | Safety chain (for 16, 20 and 24 Blade Models).....                                |              |                 |                  |                                         |                                              | Price Upon Request          |                    |
| FA-01-0015                                           | Safety Chain (for 28, 32, and 36 Blade Models).....                               |              |                 |                  |                                         |                                              | Price Upon Request          |                    |
| RECOMMENDED TIRE SIZE                                |                                                                                   |              |                 |                  |                                         |                                              |                             |                    |
| 4 - 12.5L x 15 Tires, 12 Ply .....                   |                                                                                   |              |                 |                  |                                         |                                              | Add 47 (21)ea               | PRICE UPON REQUEST |
| Note: 8 Ply tires permissible on 14'4" and smaller   |                                                                                   |              |                 |                  |                                         |                                              |                             |                    |
| 36X1200-11100 List Per Blade                         |                                                                                   |              |                 |                  |                                         |                                              |                             |                    |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**

**Amco**

MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

# DOUBLE OFFSET TANDEM

## MODEL "F15B"

16'6", 18'0" 19'6", 21'0", 24'0" Sizes

(General Purpose)

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                             |                                                                                                                       |                          |                                                                                                                    |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>               | 1-1/2" square high carbon, cold rolled steel                                                                          | <b>BEARINGS:</b>         | Protect-O-Shield®, 1-1/2" square bore<br>repeasable ball type, toggle mounted<br>with zerk guards and wear guards. |
| <b>BLADES:</b>              | 22" x 1/4" Plain diminishing with two<br>feathering blades on rear gangs.                                             | <b>WHEELS:</b>           | 4 - 15 x 8 center section<br>2 - 15 x 8 wing section<br>*4 - 15 x 8 wing section (21' x 24' ONLY)                  |
| <b>SCRAPER:</b>             | High carbon replaceable blades on heavy duty<br>shanks, mounted with grade 5 bolts on high<br>carbon angle iron bars. | <b>CLEVIS:</b>           | Reversible ductile iron                                                                                            |
| <b>TONGUE:</b>              | 90" long with tongue jack and reversible<br>ductile iron clevis.                                                      | <b>WRENCH:</b>           | 1 for gang bolt                                                                                                    |
| <b>HYDRAULIC CYLINDERS:</b> | 2 - 4" x 8" with depth control<br>(3000 PSI) 2 - 4" x 24" for folding wings                                           | <b>DISC SPACING:</b>     | 9 inches                                                                                                           |
| <b>HYDRAULIC HOSES:</b>     | 1/4" complete to front of main frame.<br>Includes hose bundle to tractor.                                             | <b>ANGLE:</b>            | Preset at 17°, No adjustment necessary                                                                             |
|                             |                                                                                                                       | <b>WEIGHT:</b>           | 122 - 140 lbs per blade<br>337 - 389 lbs. per foot                                                                 |
|                             |                                                                                                                       | <b>TRANSPORT WIDTH:</b>  | 12'6"                                                                                                              |
|                             |                                                                                                                       | <b>TRANSPORT HEIGHT:</b> | 12'6"                                                                                                              |

| MODEL NO.                                                                         | Cutting Width | No. of Discs | No. of Bearings | Disc Size & Type | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price    |
|-----------------------------------------------------------------------------------|---------------|--------------|-----------------|------------------|---------------------------------|-----------------------------|-----------------------|
| F15B-4622                                                                         | 16'6" (5.03m) | 46           | 16              | 22" Plain        | 115-130 (86-97)                 | 6387 (2903)                 | \$ 17,578.00          |
| F15B-5022                                                                         | 18'0" (5.49m) | 50           | 16              | 22" Plain        | 120-140 (89-104)                | 7101 (3228)                 | 18,000.00             |
| F15B-5422                                                                         | 19'6" (5.95m) | 54           | 16              | 22" Plain        | 125-150 (92-112)                | 7375 (3352)                 | 18,924.00             |
| F15B-5822*                                                                        | 21'0" (6.41m) | 58           | 16              | 22" Plain        | 135-165 (101-123)               | 8100 (3682)                 | 19,739.00             |
| F15B-6622*                                                                        | 24'0" (7.32m) | 66           | 20              | 22" Plain        | 150-180 (112-134)               | 9060 (4118)                 | 21,128.00             |
| Note: For split gangs, see page 16                                                |               |              |                 |                  |                                 |                             |                       |
| <b>OPTIONAL EQUIPMENT</b>                                                         |               |              |                 |                  |                                 |                             |                       |
| Shock absorber gang risers in lieu of Std. cast gang risers,<br>per bearing ..... |               |              |                 |                  |                                 | Add 18 (8) ea.              | Add 43.25 ea          |
| (Note: AMCO recommends 1/4" (6mm) blades for use with shock absorber gangs.)      |               |              |                 |                  |                                 |                             |                       |
| 22" x 6 Ga. cutout blades in lieu of standard 22" .....                           |               |              |                 |                  |                                 | Ded 9.0 (4.1) ea            | Ded 7.00 ea           |
| 22" x 6 Ga. (6mm) plain blades in lieu of standard 22" .....                      |               |              |                 |                  |                                 | Ded 8.6 (3.9) ea            | Ded 8.00 ea           |
| 22" x 1/4" (6mm) cutout blades in lieu of standard 22" .....                      |               |              |                 |                  |                                 | Ded 1.9 (.9) ea             | Add 1.00 ea           |
| 24" x 1/4" (6mm) plain blades in lieu of standard 22" .....                       |               |              |                 |                  |                                 | Add 6.0 (2.8) ea            | Add 7.00 ea           |
| 24" x 1.4" (6mm) cutout blades in lieu of standard 22" .....                      |               |              |                 |                  |                                 | Add 4.0 (1.8) ea            | Add 7.65 ea           |
| <b>RECOMMENDED TIRE SIZE</b>                                                      |               |              |                 |                  |                                 |                             |                       |
| 11L x 15, 8 Ply Tires, Center Section .....                                       |               |              |                 |                  |                                 | Add 35 (15.9)               | PRICE UPON<br>REQUEST |
| 11L x 15, 6 or 8 Ply Tires, Wing Section .....                                    |               |              |                 |                  |                                 | Add 35 (15.9)               |                       |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**

**Amco**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

**MANUFACTURING, INC.**



# DOUBLE OFFSET TANDEM

## MODEL "F15"

24'0", 27'0", AND 30'0" Sizes

(General Purpose)

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                             |                                                                                                                                                                                     |                          |                                                                                                                |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>               | 1-1/2" square high carbon, cold rolled steel                                                                                                                                        | <b>HYDRAULIC HOSE:</b>   | 1/4" complete to front of main frame, includes hoses to tractor                                                |
| <b>BLADES:</b>              | 24" x 1/4" Plain with diminishing leveling blades                                                                                                                                   | <b>BEARINGS:</b>         | Protect-O-Shield®, 1-1.2" square bore regreasable ball type, toggle mounted with zerkl guards and wear guards. |
| <b>SCRAPER:</b>             | High carbon replaceable blades on heavy duty shanks, mounted with grade 5 bolts on high carbon angle iron bars                                                                      | <b>WHEELS</b>            | 4 - 15 x 10 center section<br>4 - 15 x 8 wing section<br>* 4 - 15 x 6 wing section 66 blade only               |
| <b>TONGUE:</b>              | 90" long with tongue jack and reversible ductile iron clevis.                                                                                                                       | <b>CLEVIS:</b>           | Reversible ductile iron                                                                                        |
| <b>HYDRAULIC CYLINDERS:</b> | 2 - 4" x 12" center lift w/DIAL-A-DEPTH depth control (3000 PSI)<br>2 - 3-1/2" x 12" wing lift w/DIAL-A-DEPTH depth control (3000 PSI)<br>2 - 4" x 24" for folding wings (3000 PSI) | <b>DISC SPACING:</b>     | 9 Inches                                                                                                       |
| <b>WRENCH:</b>              | 1 for gang bolt                                                                                                                                                                     | <b>ANGLE:</b>            | Preset at 17°, No adjustment necessary                                                                         |
|                             |                                                                                                                                                                                     | <b>WEIGHT:</b>           | 135 - 145 lbs. per blade<br>375 - 390 lbs. per foot                                                            |
|                             |                                                                                                                                                                                     | <b>TRANSPORT WIDTH:</b>  | Under 14'6"                                                                                                    |
|                             |                                                                                                                                                                                     | <b>TRANSPORT HEIGHT:</b> | 12'0" on 27' Model<br>13'3" on 30' Model                                                                       |

4090-3%

| MODEL NO.                                                                       | Cutting Width | No. of Discs | No. of Bearings | Disc Size & Type | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price     |
|---------------------------------------------------------------------------------|---------------|--------------|-----------------|------------------|---------------------------------|-----------------------------|------------------------|
| F15-6624*                                                                       | 24'0" (7.32m) | 66           | 20              | 24" Plain        | 180-220 (134-164)               | 11311 (5141)                | \$ 26,726.00           |
| F15-7424                                                                        | 27'0" (8.24m) | 74           | 22              | 24" Plain        | 180-220 (134-164)               | 11715 (5325)                | 27,955.00              |
| F15-8224                                                                        | 30'0" (9.15m) | 82           | 22              | 24" Plain        | 190-235 (142-175)               | 12367 (5621)                | 29,170.00              |
| Note: For split gangs, see page 16                                              |               |              |                 |                  |                                 |                             |                        |
| <b>OPTIONAL EQUIPMENT</b>                                                       |               |              |                 |                  |                                 |                             |                        |
| Shock absorber gang risers in lieu of Std. cast gang risers, per bearing .....  |               |              |                 |                  |                                 | Add 18 (8) ea               | Add 43.25 ea           |
| (Note: AMCO recommends 1/4" (6mm) blades for use with shock absorber gangs.)    |               |              |                 |                  |                                 |                             |                        |
| (4)HD 8 hole hub and wheels in lieu of Std. 6 hole on center section only ..... |               |              |                 |                  |                                 | Add 20.0 (9.1) ea           | Add 392.00             |
| 15 x 10 wheels in lieu of 15 x 8 standard .....                                 |               |              |                 |                  |                                 | Add 6.0 (2.7) ea            | Add 8.80 ea            |
| 22" x 6 Ga. plain blades in lieu of standard 24" .....                          |               |              |                 |                  |                                 | Ded 14.6 (6.6) ea           | Ded 13.70 ea           |
| 22" x 6 Ga. cutout blades in lieu of standard 24" .....                         |               |              |                 |                  |                                 | Ded 15.0 (6.8) ea           | Ded 13.70 ea           |
| <del>22" x 1/4" (6mm) plain blades in lieu of standard 24" .....</del>          |               |              |                 |                  |                                 | <del>Ded 6.0 (2.7) ea</del> | <del>Ded 5.50 ea</del> |
| 22" x 1/4" (6mm) cutout blades in lieu of standard 24" .....                    |               |              |                 |                  |                                 | Ded 7.9 (3.6) ea            | Ded 6.70 ea            |
| 24" x 1/4" (6mm) cutout blades in lieu of standard 24" .....                    |               |              |                 |                  |                                 | Ded 2.0 (.9) ea             | Add 1.00 ea            |
| <b>RECOMMENDED TIRE SIZE</b>                                                    |               |              |                 |                  |                                 |                             |                        |
| * 4 - 9.5L x 15 Tires, 6 or 8 Ply, for wings 66 blade only .....                |               |              |                 |                  |                                 | Add 21 (12.3) ea            | PRICE                  |
| 4 - 12.5 x 15 Tires, 8 Ply, for center .....                                    |               |              |                 |                  |                                 | Add 47 (21) ea              | UPON                   |
| 4 - 11L x 15 Tires, 6 or 8 Ply, for wings .....                                 |               |              |                 |                  |                                 | Add 35 (15.9) ea            | REQUEST                |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

# DOUBLE OFFSET TANDEM

## MODEL "F15"

34'6" AND 39'0" Sizes

(Heavy Primary Tillage)

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                             |                                                                                                                                                                          |                          |                                                                                                               |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>               | 1-1/2" square high carbon, cold rolled steel                                                                                                                             | <b>HYDRAULIC HOSES:</b>  | 1/4" complete to front of main frame; includes hoses to tractor                                               |
| <b>DISC:</b>                | 24" x 1/4" Plain                                                                                                                                                         | <b>BEARINGS:</b>         | Protect-O-Shield®, 1-1/2" square bore regreaseable ball type, toggle mounted with Zerk guards and Wear guards |
| <b>BLADES:</b>              | Diminishing with two feathering blades on rear gangs                                                                                                                     | <b>WHEELS:</b>           | 4 - 15 x 10 center section - 8 hole HD<br>4 - 15 x 8 wing sections - 6 Hole                                   |
| <b>SCRAPER:</b>             | High carbon replaceable blades on heavy duty shanks, mounted with grade 5 bolts on thigh carbon angle iron bars.                                                         | <b>WRENCH:</b>           | 1 for gang bolt                                                                                               |
| <b>TONGUE:</b>              | 90" long with tongue jack and reversible ductile iron clevis                                                                                                             | <b>DISC SPACING:</b>     | 9 Inches                                                                                                      |
| <b>HYDRAULIC CYLINDERS:</b> | 2 - 4" x 12" center lift w/DIAL-A-DEPTH depth control (2500 PSI)<br>2 - 3-1/2" x 12" wing lift w/DIAL-A-DEPTH depth control<br>4 - 4" x 24" for folding wings (2500 PSI) | <b>ANGLE:</b>            | Preset at 17°, No adjustment necessary.                                                                       |
|                             |                                                                                                                                                                          | <b>WEIGHT:</b>           | 135 - 145 lbs. per blade<br>375 - 390 lbs. per foot                                                           |
|                             |                                                                                                                                                                          | <b>TRANSPORT WIDTH:</b>  | Under 17'6"                                                                                                   |
|                             |                                                                                                                                                                          | <b>TRANSPORT HEIGHT:</b> | 14'0" on 34'6" Model<br>15'9" on 39" Model                                                                    |
|                             |                                                                                                                                                                          | <b>NOTE:</b>             | Inside Hub - 8 Hole Heavy Duty                                                                                |

| MODEL NO.                          | Cutting Width                                                                  | No. of Discs | No. of Bearings | Disc Size & Type | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|------------------------------------|--------------------------------------------------------------------------------|--------------|-----------------|------------------|---------------------------------|-----------------------------|--------------------|
| F15-9424                           | 34'6" (10.52m)                                                                 | 94           | 26              | 24" Plain        | 230-280 (172-209)               | 14855                       | \$ 34,772.00       |
| F15-10624                          | 39'0" (11.90m)                                                                 | 106          | 30              | 24" Plain        | 250-300 (186-224)               | 16103                       | 37,000.00          |
| Note: For split gangs, see page 16 |                                                                                |              |                 |                  |                                 |                             |                    |
| <b>OPTIONAL EQUIPMENT</b>          |                                                                                |              |                 |                  |                                 |                             |                    |
| AN-70-0001                         | Shock absorber gang risers in lieu of Std. cast gang risers, per bearing ..... |              |                 |                  |                                 | Add 18 ea                   | Add 43.25 ea       |
|                                    | (NOTE: AMCO recommends 1.4" (6mm) blades for use with shock absorber gangs.)   |              |                 |                  |                                 |                             |                    |
|                                    | 15 x 10 wheels in lieu of standard 15 x 8 for wings .....                      |              |                 |                  |                                 | Add 6 ea                    | Add 8.80 ea        |
|                                    | 22" x 6 Ga. Plain blades in lieu of standard 24" .....                         |              |                 |                  |                                 | Ded 14.6 ea                 | Ded 13.70 ea       |
|                                    | 22" x 6 Ga. cutout blades in lieu of standard 24" .....                        |              |                 |                  |                                 | Ded 15.0 ea                 | Ded 13.70 ea       |
|                                    | 22" x 1/4" (6mm) plain blades in lieu of standard 24" .....                    |              |                 |                  |                                 | Ded 6.0 ea                  | Ded 5.50 ea        |
|                                    | 22" x 1/4" (6mm) cutout blades in lieu of standard 24" .....                   |              |                 |                  |                                 | Ded 7.9 ea                  | Ded 6.75 ea        |
|                                    | 24" x 1/4" (6mm) cutout blades in lieu of standard 24" .....                   |              |                 |                  |                                 | Ded 2.0 ea                  | Add 1.00 ea        |
| <b>RECOMMENDED TIRESIZE</b>        |                                                                                |              |                 |                  |                                 |                             |                    |
| 195-00<br>94 00                    | 4 - 12.5L x 15 Tires, 12 Ply, for center .....                                 |              |                 |                  |                                 | Add 47 (21) ea              | PRICE UPON REQUEST |
|                                    | 4 - 11L x 15 Tires, 6 or 8 Ply, for wings .....                                |              |                 |                  |                                 | Add 35 (15.9) ea            |                    |

AMCO PL. Effective March 15, 2004

P.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**

**Amco**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

**MANUFACTURING, INC.**



# F15 - SPRING STEEL SCRAPER OPTIONS

## Optional: EXTRA HEAVY DUTY SPRING STEEL SCRAPERS FOR F15 HARROWS

3" x 2" x 3/8" high carbon angle iron bars

3/8" x 2" spring steel scrapers

3/16" x 6-1/2" x 8" high carbon scraper blades

**THESE EXTRA HEAVY DUTY SPRING STEEL SHANK SCRAPERS  
ARE RECOMMENDED FOR HEAVY SOIL CONDITIONS**

| ORDERED IN LIEU OF STANDARD<br>(on factory assembled units) |                      |                    |              |                   | ORDERED AS REPLACEMENT<br>BUNDLE (field kit) |        |            |
|-------------------------------------------------------------|----------------------|--------------------|--------------|-------------------|----------------------------------------------|--------|------------|
| Harrow Model Number                                         | Harrow Cutting Width | Scraper Kit Number | Weight (Add) | List Price (Add)  | Bundle Number                                | Weight | List Price |
| F15B - 46 Blade                                             | 16'6"                | BC-14-0005         | 131          | \$ 505.00         | BC-14-0019                                   | 486    | \$1,190.00 |
| F15B - 50 Blade                                             | 18'0"                | BC-14-0006         | 145          | <del>555.00</del> | BC-14-0020                                   | 532    | 1,294.00   |
| F15B - 54 Blade                                             | 19'6"                | BC-14-0007         | 155          | 599.00            | BC-14-0021                                   | 580    | 1,401.00   |
| F15B - 58 Blade                                             | 21'0"                | BC-14-0008         | 172          | 649.00            | BC-14-0022                                   | 627    | 1,509.00   |
| F15B - 66 Blade                                             | 24'0"                | BC-14-0009         | 199          | 743.00            | BC-14-0023                                   | 721    | 1,708.00   |

| ORDERED IN LIEU OF STANDARD<br>(on factory assembled units) |                      |                    |              |                     | ORDERED AS REPLACEMENT<br>BUNDLE (field kit) |        |            |
|-------------------------------------------------------------|----------------------|--------------------|--------------|---------------------|----------------------------------------------|--------|------------|
| Harrow Model Number                                         | Harrow Cutting Width | Scraper Kit Number | Weight (Add) | List Price (Add)    | Bundle Number                                | Weight | List Price |
| F15 - 66 Blade                                              | 24'                  | BC-14-0037         | 280          | <del>\$750.00</del> | BC-14-0039                                   | 726    | \$1,802.00 |
| F15 - 74 Blade                                              | 27'                  | BC-14-0010         | 226          | <del>\$38.00</del>  | BC-14-0024                                   | 815    | 1,904.00   |
| F15 - 82 Blade                                              | 30'                  | BC-14-0011         | 253          | <del>925.00</del>   | BC-14-0025                                   | 904    | 2,116.00   |

| ORDERED IN LIEU OF STANDARD<br>(on factory assembled units) |                      |                    |              |                     | ORDERED AS REPLACEMENT<br>BUNDLE (field kit) |        |            |
|-------------------------------------------------------------|----------------------|--------------------|--------------|---------------------|----------------------------------------------|--------|------------|
| Harrow Model Number                                         | Harrow Cutting Width | Scraper Kit Number | Weight (Add) | List Price (Add)    | Bundle Number                                | Weight | List Price |
| F15 - 94 Blade                                              | 34'6"                | BC-14-0012         | 290          | \$1,071.00          | BC-14-0026                                   | 1034   | \$2,432.00 |
| F15 - 106 Blade                                             | 39'0"                | BC-14-0013         | 327          | <del>1,222.00</del> | BC-14-0027                                   | 1180   | 2,748.00   |

AMCO PL Effective March 15, 2004

E.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**MANUFACTURING, INC.**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

[www.amcomfg.com](http://www.amcomfg.com)

## F15 (24' - 39') SPLIT GANGS

This price sheet reflects Split Gangs in lieu of standard on following units:

|                  |                       |                      |                    |
|------------------|-----------------------|----------------------|--------------------|
| <b>F15B - 66</b> | <b>Blade (24' 0")</b> | <b>Add \$ 977.00</b> | <b>Add 4 Brgs.</b> |
| <b>F15 - 66</b>  | <b>Blade (24' 0")</b> | <b>Add 977.00</b>    | <b>Add 4 Brgs.</b> |
| <b>F15 - 74</b>  | <b>Blade (27' 0")</b> | <b>Add 977.00</b>    | <b>Add 4 Brgs.</b> |
| <b>F15 - 82</b>  | <b>Blade (30' 0")</b> | <b>Add 977.00</b>    | <b>Add 4 Brgs.</b> |
| <b>F15 - 94</b>  | <b>Blade (34' 6")</b> | <b>Add 1,467.00</b>  | <b>Add 6 Brgs.</b> |
| <b>F15 - 106</b> | <b>Blade (39' 0")</b> | <b>Add 1,467.00</b>  | <b>Add 6 Brgs.</b> |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**MANUFACTURING, INC.**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

[www.amcomfg.com](http://www.amcomfg.com)



# DOUBLE OFFSET TANDEM

## MODEL "F17B"

(General Purpose)

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                     |                                                                                                                |                             |                                                                                                               |
|---------------------|----------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>       | Four 1-1/2" square high carbon, cold rolled steel                                                              | <b>TONGUE:</b>              | 70 inches long with tongue jack and reversible clevis.                                                        |
| <b>DISC:</b>        | 22" x 1/4" Plain                                                                                               | <b>BEARINGS:</b>            | Protect-O-Shield®, 1-1/2" square bore regreasable ball type, toggle mounted with zerk guards and wear guards. |
| <b>BLADES:</b>      | Diminishing with two feathering blades on rear gangs                                                           | <b>WHEELS:</b>              | 2 - 15 x 8 with heavy duty 6 bolt hubs<br>9'3", 10'6", 12'0"<br>4 - 15 x 8 13'6" and 15'0"                    |
| <b>SPACING:</b>     | 9 Inches                                                                                                       | <b>WEIGHT:</b>              | 106 - 120 lbs. per blade<br>296 - 337 lbs. per foot                                                           |
| <b>SCRAPER:</b>     | High carbon replaceable blades on heavy duty shanks, mounted with grade 5 bolts on high carbon angle iron bars | <b>TRANSPORT WIDTH:</b>     | Width of cut plus 18 Inches                                                                                   |
| <b>GANG ANGLE:</b>  | Adjustable - 18° - 22° Front<br>17° - 21° Rear                                                                 | <b>HYDRAULIC CYLINDERS:</b> | 4" x 8" x 1-1/2" with stroke control (3000 PSI) Includes hose bundle to tractor                               |
| <b>WRENCH</b>       | One for Gang Bolts                                                                                             |                             |                                                                                                               |
| <b>WHEEL TREAD:</b> | 84 Inches on center                                                                                            |                             |                                                                                                               |

25-5-5

| MODEL NO.                                                                     | Cutting Width                                                 | No. of Discs | No. of Bearings | Disc Size & Type | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Factory List Price |
|-------------------------------------------------------------------------------|---------------------------------------------------------------|--------------|-----------------|------------------|---------------------------------|-----------------------------|--------------------|
| F17B-2622                                                                     | 9'3" (2.82m)                                                  | 26           | 8               | 22" Plain        | 50 - 70 (37 - 52)               | 3360 (1527)                 | \$ 8,247.00        |
| F17B-3022                                                                     | 10'6" (3.20m)                                                 | 30           | 8               | 22" Plain        | 60 - 80 (45 - 60)               | 3644 (1656)                 | 8,618.00           |
| F17B-3422                                                                     | 12'0" (3.66m)                                                 | 34           | 8               | 22" Plain        | 70 - 90 (52 - 67)               | 3928 (1785)                 | 9,113.00           |
| F17B-3822*                                                                    | 13'6" (4.12m)                                                 | 38           | 12              | 22" Plain        | 80 - 100 (60 - 75)              | 4708 (2140)                 | 10,877.00          |
| F17B-4222*                                                                    | 15'0" (4.68m)                                                 | 42           | 12              | 22" Plain        | 90 - 115 (67 - 86)              | 5022 (2283)                 | 11,272.00          |
| F17B-4622*                                                                    | 16'6" (5.15m)                                                 | 46           | 12              | 22" Plain        | 105 - 130 (79 - 98)             | 5336 (2425)                 | 11,668.00          |
| *Includes 2 outrigger bars and clamps                                         |                                                               |              |                 |                  |                                 |                             |                    |
| <b>OPTIONAL EQUIPMENT</b>                                                     |                                                               |              |                 |                  |                                 |                             |                    |
| Shock absorber gang risers in lieu of Std. cast gang risers, per bearing..... |                                                               |              |                 |                  |                                 | Add 18 (8) ea               | Add 43.25 ea       |
| (NOTE: AMCO recommends 1.4" (6mm) blades for use with stock absorber gangs.)  |                                                               |              |                 |                  |                                 |                             |                    |
| AN-20-0001                                                                    | 15 x 10 wheels in lieu of standard 15 x 8 .....               |              |                 |                  |                                 | Add 6 (2.7) ea              | Add 8.80 ea        |
| BR-14-0001                                                                    | Dual wheels in lieu of single on 9'3", 10'6", and 12'0" ..... |              |                 |                  |                                 | Add 106 (48) ea             | Add 292.00 ea      |
|                                                                               | 22" x 3/16" cutout blades in lieu of standard 22" .....       |              |                 |                  |                                 | Ded 9.0 (4.1) ea            | Ded 7.00 ea        |
|                                                                               | 22" x 3/16" plain blades in lieu of standard 22" .....        |              |                 |                  |                                 | Ded 8.6 (3.9) ea            | Ded 8.00 ea        |
|                                                                               | 22" x 1/4" (6mm) cutout blades in lieu of standard 22" .....  |              |                 |                  |                                 | Ded 1.9 (.9) ea             | Add 1.00 ea        |
|                                                                               | 24" x 1/4" (6mm) plain blades in lieu of standard 22" .....   |              |                 |                  |                                 | Add 6.0 (2.8) ea            | Add 7.00 ea        |
|                                                                               | 24" x 1/4" (6mm) cutout blades in lieu of standard 22" .....  |              |                 |                  |                                 | Add 4.0 (1.8) ea            | Add 7.65 ea        |
| FA-01-0014                                                                    | Safety Chains .....                                           |              |                 |                  |                                 | Add 9 (4.1) ea              | Price On Request   |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

## F17B ATTACHMENTS AND OPTIONS

### Optional: EXTRA HEAVY DUTY SPRING STEEL SCRAPERS

3" x 2" x 3/8" high carbon angle iron bars

3/8" x 2" spring steel scraper shanks

3/16" x 6-1/2" x 8" high carbon scraper blades

**THESE EXTRA HEAVY DUTY SPRING STEEL SHANK SCRAPERS  
ARE RECOMMENDED FOR HEAVY SOIL CONDITIONS**

| ORDERED IN LIEU OF STANDARD<br>(on factory assembled units) |                            |                       |                 |                     | ORDERED AS REPLACEMENT<br>BUNDLE (field kit) |        |            |
|-------------------------------------------------------------|----------------------------|-----------------------|-----------------|---------------------|----------------------------------------------|--------|------------|
| Harrow Model<br>Number                                      | Harrow<br>Cutting<br>Width | Scraper Kit<br>Number | Weight<br>(Add) | List Price<br>(Add) | Bundle<br>Number                             | Weight | List Price |
| F17B-26 Blade                                               | 9'3"                       | BC-14-0014            | 69              | \$ 234.00           | BC-14-0028                                   | 254    | \$673.00   |
| F17B-30 Blade                                               | 10'6"                      | BC-14-0015            | 81              | 273.00              | BC-14-0029                                   | 301    | 776.00     |
| F17B-34 Blade                                               | 12'0"                      | BC-14-0016            | 94              | 316.00              | BC-14-0030                                   | 349    | 879.00     |
| F17B-38 Blade                                               | 13'6"                      | BC-14-0017            | 106             | 362.00              | BC-14-0031                                   | 395    | 983.00     |
| F17B-42 Blade                                               | 15'0"                      | BC-14-0018            | 119             | 402.00              | BC-14-0032                                   | 442    | 1,088.00   |
| F17B-46 Blade                                               | 16'6"                      | BC-14-0019            | 132             | 442.00              | BC-14-0038                                   | 489    | 1,192.00   |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

[www.amcomfg.com](http://www.amcomfg.com)

**MANUFACTURING, INC.**



## SERRIATOR® (SQUARE) BLADES IN LIEU OF CONVENTIONAL BLADES

|                                                        |                                           |          |
|--------------------------------------------------------|-------------------------------------------|----------|
| <b>ALL F41 SERIES:</b>                                 |                                           |          |
| 22" X .256                                             | Serriator® blades in lieu of ..... Add    | \$ 8.40  |
| 24" X .256                                             | Serriator® blades in lieu of ..... Add    | 20.45    |
| 26" X 5/16"                                            | Serriator® blades in lieu of ..... Add    | 41.35    |
| <b>ALL J41 SERIES:</b>                                 |                                           |          |
| 22" X .256                                             | Serriator® blades in lieu of ..... Deduct | \$ 1.00  |
| 24" X .256                                             | Serriator® blades in lieu of ..... Add    | 10.85    |
| 26" X 5/16"                                            | Serriator® blades in lieu of ..... Add    | 31.75    |
| <b>ALL J16 - 148 - 185 SERIES, F42, J42, J43, J44:</b> |                                           |          |
| 24" X .256                                             | Serriator® blades in lieu of ..... Add    | \$ 12.55 |
| 26" X 5/16"                                            | Serriator® blades in lieu of ..... Add    | 33.50    |
| <b>ALL F15B &amp; F17B:</b>                            |                                           |          |
| 22" X .256                                             | Serriator® blades in lieu of ..... Add    | \$ 9.60  |
| 24" X .256                                             | Serriator® blades in lieu of ..... Add    | 21.60    |
| 26" X 5/16"                                            | Serriator® blades in lieu of ..... Add    | 42.55    |
| <b>ALL F15 - 66B thru 106B:</b>                        |                                           |          |
| 22" X .256                                             | Serriator® blades in lieu of ..... Add    | \$ 1.00  |
| 24" X .256                                             | Serriator® blades in lieu of ..... Add    | 12.55    |
| 26" X 5/16"                                            | Serriator® blades in lieu of ..... Add    | 33.50    |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**

**MANUFACTURING, INC.****AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

# HYDRAULIC TERRACING PLOW

## MODELS "TJ3"

10-1/2" Spacing

### STANDARD SPECIFICATIONS

**AXLES:** 1-1/2" square, high carbon cold rolled steel

**BLADES:** 26" x 1/4" (6mm) Plain with 10" back-up blades on inside and outside blades, with two 20" x 1/4" end blades with 10" back-up blades.

**SCRAPER:** High carbon replaceable and adjustable blades with 3/8" x 2" heat treated spring steel shanks, mounted to 3" x 2" x 3/8" high carbon angle iron bar

**GANG FRAME:** 6" x 4" x 3/8" Welded Tube

**GANG ANGLE:** Adjustable from 21° to 29°

**GANG TILT:** Hydraulically controlled from 18° down to 43° up

**HYDRAULIC CYLINDERS:** Two 4" x 16" independent (3000PSI)

**HYDRAULIC HOSES:** Four 3/8" dia. hoses to mount from hydraulic cylinders to tractor

**TILT INDICATOR:** Allows positive setting of gangs at desired tilt from drivers seat

**MAIN FRAME:** 7" x 7" x 3/8" tool bar with ASAE Cat. III hitch for quick coupler and conventional three point

**BEARINGS:** Protect "O" Shield®, extra heavy duty 1-1/2" square bore, greasable ball type, toggle mounted. Two year guarantee on bearings. Includes zerkl guards and wear guards.

**SPACE SPOOLS:** Fabricated steel

**TRANSPORT WIDTH:** 9'

**WRENCH:** One for gang bolt nut

**WEIGHT PER FOOT:** 190 pounds

**WEIGHT PER BLADE:** 201 pounds

**PARKING STANDS:** Two

| MODEL NO.                                                                                                                                                                                                         | Width of Unit | No. of Bearings | No. of Blades | Blade Spacing | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Suggested List Price |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-----------------|---------------|---------------|---------------------------------|-----------------------------|----------------------|
| TJ3-1826                                                                                                                                                                                                          | 16'10"        | 6               | 18            | 10-1/2"       | 130-200                         | 3212 (1460)                 | \$ 9,181.00          |
| <p align="center"><b>OPTIONAL EQUIPMENT</b></p> <p>Shock Absorber gang risers in lieu of standard cast gang risers, add per bearing .....</p> <p>26" x 1/4" (6mm) cutout blade in lieu of standard (16) .....</p> |               |                 |               |               |                                 |                             |                      |
|                                                                                                                                                                                                                   |               |                 |               |               |                                 | Add 18 (8.2) ea             | Add 47.30 ea         |
|                                                                                                                                                                                                                   |               |                 |               |               |                                 | Desl 1.5 (.7) ea            | Add 3.00 ea          |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**

**Amco**

MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# HYDRAULIC LEVEE PLOWS


## MODELS "LF6" and "LJ6"

9" or 10-1/2" Spacing

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                             |                                                                                                                                                                                             |                         |                                                                                                                                           |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>               | 1-1/2" square, high carbon cold rolled steel                                                                                                                                                | <b>GANG ANGLE:</b>      | 18° to 28°                                                                                                                                |
| <b>BLADES:</b>              | 24" x 1/4" (6mm) Plain with 10" back-up blade behind outside blade                                                                                                                          | <b>TILT INDICATOR:</b>  | One to mount with 3" x 8" hydraulic cylinder for adjustments on the go                                                                    |
| <b>SCRAPER:</b>             | High carbon replaceable and adjustable blades with 3/8" x 2" heat treated spring shanks, mounted to 3" x 2" x 3/8" high carbon angle iron bar with flange lock nuts and 5/8" carriage bolts | <b>MAINFRAME:</b>       | 7" x 4" x 3/8" tool bar with ASAE Cat. II and Cat. III hitch for quick coupler and conventional three point                               |
| <b>GANG TILT:</b>           | Hydraulic controlled-on-the-go adjustment                                                                                                                                                   | <b>BEARINGS:</b>        | Four Protect 'O' Shield®, extra heavy duty 1-1/2" square bore, greaseable ball type, toggle mounted, includes zerk guards and wear guards |
| <b>HYDRAULIC CYLINDERS:</b> | One 3" x 8" and one 3-1/4" x 8" rephasing cylinders to control tilt                                                                                                                         | <b>SPACING:</b>         | 9" on LF6, 10-1/2" on LJ6                                                                                                                 |
| <b>HYDRAULIC HOSES:</b>     | 3/8" dia. hoses to mount from hydraulic cylinders to tractor                                                                                                                                | <b>SPACER SPOOLS:</b>   | Fabricated steel                                                                                                                          |
|                             |                                                                                                                                                                                             | <b>TRANSPORT WIDTH:</b> | 10'6" on 8-blade models<br>12'6" on 10-blade models                                                                                       |
|                             |                                                                                                                                                                                             | <b>WRENCH:</b>          | One for gang bolt nut                                                                                                                     |

| MODEL NO.  | Adjustable Cutting Width                                                                                                                           | No. of Blades | Blade Spacing | Drawbar HP Required | Approximate Weight (lbs (kg)) | Approximate Suggested List Price |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------------|---------------------|-------------------------------|----------------------------------|
|            |  9" SPACING                                                      |               |               |                     |                               |                                  |
| LF6-824    | 8'11" to 9'11"                                                                                                                                     | 8             | 9"            | 80-125              | 2060 (934)                    | \$ 6196.00                       |
| LF6-1024   | 10'5" to 11'5"                                                                                                                                     | 10            | 9"            | 90-150              | 2260 (1025)                   | 6541.00                          |
|            | 10-1/2" SPACING                                                                                                                                    |               |               |                     |                               |                                  |
| LJ6-824    | 9'5" to 10'5"                                                                                                                                      | 8             | 10-1/2"       | 85-140              | 2160 (980)                    | 76235.00                         |
| LJ6-1024   | 11'1" to 12'1"                                                                                                                                     | 10            | 10-1/2"       | 100-160             | 2360 (1070)                   | 6581.00                          |
|            | OPTIONAL EQUIPMENT                                                                                                                                 |               |               |                     |                               |                                  |
| AD-01-0001 | Feathering blade (set of 2) with scraper and back-up blade .....<br>(Note: Feathering blade requires two drilled and tapped bumper washers #9579A) |               |               |                     | Add 74 (34)                   | Add 368.00                       |
|            | 24" x 1/4" (6mm) cutout blades in lieu of standard 24" .....                                                                                       |               |               |                     | Ded 1.3 (.6) ea               | Add 1.00 ea                      |
|            | 26" x 1/4" (6mm) plain blades in lieu of standard 24" .....                                                                                        |               |               |                     | Add 5.8 (2.6) ea              | Add 8.25 ea                      |
|            | 26" x 1/4" (6mm) cutout blades in lieu of standard 24" .....                                                                                       |               |               |                     | Add 3.8 (1.7) ea              | Add 12.00 ea                     |

### OTHER STANDARD FEATURES

Two parking stands.  
Adjustable cutting width.  
Follow the levee feature-gangs can shift independent from the tractor to follow true on sharply curving levees.

Gangs easily reverse to tear down levees.  
Ductile iron bearing risers.  
These Levee Plows feature our exclusive Protect 'O' Shield bearing with a TWO year warranty.

AMCO Pl. Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**

**Amco**

MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

# MANUAL LEVEE PLOWS

## MODELS "MLF6" and "MLJ6"

9" or 10-1/2" Spacing

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                    |                                                                                                                                                                                             |                         |                                                                                                                                           |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>AXLES:</b>      | 1-1/2" square, high carbon cold rolled steel                                                                                                                                                | <b>MAINFRAME:</b>       | 7" x 4" x 3/8" tool bar with ASAE Cat. II and Cat. III hitch for quick coupler and conventional three point                               |
| <b>BLADES:</b>     | 24" x 1/4" (6mm) Plain with 10" back-up blade behind outside blade                                                                                                                          | <b>BEARINGS:</b>        | Four Protect-O-Shield®, extra heavy duty 1-1/2" square bore, greaseable ball type, toggle mounted, includes zerker guards and wear guards |
| <b>SCRAPER:</b>    | High carbon replaceable and adjustable blades with 3/8" x 2" heat treated spring shanks, mounted to 3" x 2" x 3/8" high carbon angle iron bar with flange lock nuts and 5/8" carriage bolts | <b>SPACING:</b>         | 9" on MLF6, 10-1/2" on MLJ6                                                                                                               |
| <b>GANG ANGLE:</b> | 18° to 28°                                                                                                                                                                                  | <b>SPACING SPOOLS:</b>  | Fabricated steel                                                                                                                          |
| <b>GANG TILT:</b>  | Manual controlled                                                                                                                                                                           | <b>TRANSPORT WIDTH:</b> | 10'6" on 8-blade models<br>12'6" on 10-blade models                                                                                       |
| <b>WRENCH:</b>     | One for gang bolt nut                                                                                                                                                                       |                         |                                                                                                                                           |

| MODEL NO.                 | Adjustable Cutting Width                                                                                                                           | No. of Blades | Blade Spacing | Drawbar HP Required | Approximate Weight lbs (kg) | Approximate Suggested List Price |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|---------------|---------------|---------------------|-----------------------------|----------------------------------|
| <b>9" SPACING</b>         |                                                                                                                                                    |               |               |                     |                             |                                  |
| MLF6-824                  | 8'11" to 9'11"                                                                                                                                     | 8             | 9"            | 80-125              | 2060 (934)                  | \$ 5,338.00                      |
| MLF6-1024                 | 10'5" to 11'5"                                                                                                                                     | 10            | 9"            | 90-150              | 2260 (1025)                 | 5,676.00                         |
| <b>10-1/2" SPACING</b>    |                                                                                                                                                    |               |               |                     |                             |                                  |
| MLJ6-824                  | 9'5" to 10'5"                                                                                                                                      | 8             | 10-1/2"       | 85-140              | 2160 (980)                  | <u>5,377.00</u>                  |
| MLJ6-1024                 | 11'1" to 12'1"                                                                                                                                     | 10            | 10-1/2"       | 100-160             | 2360 (1070)                 | 5,716.00                         |
| <b>OPTIONAL EQUIPMENT</b> |                                                                                                                                                    |               |               |                     |                             |                                  |
| AD-01-0007                | Feathering blade (set of 2) with scraper and back-up blade .....<br>(Note: Feathering blade requires two drilled and tapped bumper washers #9579A) |               |               |                     | Add 74                      | Add 360.00                       |
|                           | 24" x 1/4" (6mm) cutout blades in lieu of standard 24" .....                                                                                       |               |               |                     | Deal 1 1/4 ea               | Add 1.00 ea                      |
|                           | 26" x 1/4" (6mm) plain blades in lieu of standard 24" .....                                                                                        |               |               |                     | Add 5 3/4 ea                | Add 8.25ea                       |
|                           | 26" x 1/4" (6mm) cutout blades in lieu of standard 24" .....                                                                                       |               |               |                     | Add 3 3/4 ea                | Add 12.00ea                      |

### OTHER STANDARD FEATURES

Two parking stands.  
Adjustable cutting width.  
Follow the levee feature-gangs can shift independent from the tractor to follow true on sharply curving levees.

Gangs easily reverse to tear down levees.  
Ductile iron bearing risers.  
These Levee Plows feature our exclusive Protect 'O' Shield bearing with a TWO year warranty.

AMCO PL Effective March 15, 2004

J.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**

**Amco**

MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amconfg.com

# AMCO DITCHER

## STANDARD SPECIFICATIONS

25-2%

3%

**CUTTERHEAD:** Adjustable from 18" to 20" Four heat treated replaceable blades.  
740 RPM rotor speed

**CUTTING DEPTH:** Adjustable by regulating depth control skid and 3 point hitch

**CHAIN CASE:** 6" x 10" with bolt on top and bottom caps.  
Uses double 80-2 press-fit, riveted, American-made chain and a case hardened 16 tooth top sprocket and a 22 tooth bottom sprocket for AD-10-18.

**IDLER SPROCKET:** Adjustable

**HITCH:** Cat. II or III three point or quick coupler

**BOLTS:** Safety shear

**PARKING STANDS:** Two

**RECOMMENDED**

**TRACTORS:** For 80 to 150 horsepower with 1000 PTO - order AMCO Ditcher Model AD-10-18 and Model AD-20-18

For 50 to 110 horsepower with 540 PTO - order AMCO Ditcher Model AD-5-18

| MODEL NO.                                                                | Description                                          | Approximate Weight lbs (kg) | Suggested List Price |
|--------------------------------------------------------------------------|------------------------------------------------------|-----------------------------|----------------------|
| AD-5-18                                                                  | Complete AMCO Ditcher for 540 PTO - 1-3/8 6-Spline   | 602 (274)                   | \$ 3,547.00          |
| AD-10-18                                                                 | Complete AMCO Ditcher for 1000 PTO - 1-3/8 21-Spline | 602 (274)                   | 3,547.00             |
| AD-20-18                                                                 | Complete AMCO Ditcher for 1000 PTO - 1-3/4 20-Spline | 602 (274)                   | 3,586.00             |
| Note: All models above with ripper shank and point as standard equipment |                                                      |                             |                      |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**MANUFACTURING, INC.**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# AMCO's Exclusive Bedding Hippers

With Protect-O-Shield® Washers  
Featuring a 2-Year Bearing Warranty

## RIGID HEAVY DUTY - 1-1/2" SQUARE GANGS

### STANDARD SPECIFICATIONS

(Metric in Parentheses)

**GANGS:** 1-1/2" square gang bolt with dual regreaseable triple lip sealed ball bearings with Protect-O-Shield® washers. One 18" x 1/4" plain blade and one 20" x 1/4" (6mm) plain blade per gang. Three position angle adjustment. Grease fitting and wear guards standard equipment.

**RIGID HITCH:** A-21M2 heavy duty mast and yoke type. Fits Cat. II and III standard and quick Coupler.

**SHANKS:** Heavy duty high clearance fabricated shanks that allow either staggered or opposed gang setting.

**P.R. DEPTH GAUGE WHEELS:** For 7x7 tool bar includes turnbuckle adjustment and 15 x 6 wheels.

**NOTE:** Scrapers and row markers are optional equipment and must be ordered separately.

| MODEL NO.  | Description                                                                                                                          | Transport Width | Approximate Drawbar HP Required | Approximate Weight lbs | Suggested List Price                      |
|------------|--------------------------------------------------------------------------------------------------------------------------------------|-----------------|---------------------------------|------------------------|-------------------------------------------|
| FB6-5A     | 6-Row 7" x 7" x 3/8" x 280" Tool Bar<br>Fits row spacing of 36" to 40"<br>DA-14-0032 Sweep Attachment                                | 23' 4"          | 100-135                         | 2869<br>396            | \$ 8878.00<br>1275.00                     |
| FB8-5A     | 8-Row 7" x 7" x 1/2" x 344" Tool Bar<br>Fits row spacing of 36" to 40"<br>DA-14-0033 Sweep Attachment                                | 28' 8"          | 130-180                         | 3841<br>396            | <del>11587.00</del><br><del>1695.00</del> |
| FB10-5A    | 10-Row 7" x 7" x 1/2" x 424" Tool Bar<br>Fits row spacing 36" to 40"<br>DA-14-0035 Sweep Attachment                                  | 35' 4"          | 160-210                         | 4703<br>792            | 14347.00<br>2532.00                       |
| FSE/G-5A   | 6-Row 7" x 7" x 1/2" x 344" Tool Bar,<br>fits row spacing of 38" to 40" and<br>skip row of 60" to 64"<br>DA-14-0032 Sweep Attachment | 28' 8"          | 100-135                         | 3349<br>396            | 9522.00<br>1275.00                        |
| FB8-7A     | 8-Row 7" x 7" x 3/8" x 280" Tool Bar<br>Fits row spacing of 30" to 32"<br>DA-14-0033 Sweep Attachment                                | 23' 4"          | 130-180                         | 3384<br>396            | 11120.00<br>1695.00                       |
| FB10-7A    | 10-Row 7" x 7" x 1/2" x 344" Tool Bar<br>Fits row spacing of 30" to 32"<br>DA-14-0034 Sweep Attachment                               | 28' 8"          | 140-200                         | 4181<br>660            | 13797.00<br>2113.00                       |
| FB12-7A    | 12-Row 7" x 7" x 1/2" x 424" Tool Bar<br>Fits row spacing of 30" to 32"<br>DA-14-0035 Sweep Attachment                               | 35' 4"          | 180-230                         | 5766<br>792            | 15463.00<br>2532.00                       |
| DA-01-0136 | Scraper (Set of 4 for 2 Rows)<br><br>Note: See page 28 for optional blades<br>in lieu of standard                                    |                 |                                 | 14                     | Add 89.00                                 |

AMCO PL Effective March 15, 2004

P.O.B. Yazoo City, Mississippi

SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE



AMCO Manufacturing, Inc.

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

MANUFACTURING, INC.

# AMCO's Exclusive Bedding Hippers

With Protect-O-Shield® Washers  
Featuring a 2-Year Bearing Warranty

## HYDRAULIC HEAVY DUTY-1-1/2" SQUARE GANGS

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

|                |                                                                                                                                                                                                                                                                              |                                                   |                                                                                      |
|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------|--------------------------------------------------------------------------------------|
| <b>GANGS:</b>  | 1-1/2" square gang bolt with dual regreasable triple lip sealed ball bearings with Protect-O-Shield® washers. One 18" x 1/4" plain blade and one 20" x 1/4" (6mm) plain blade per gang. Three position angle adjustment. Grease fittings and wear guards standard equipment. | <b>HITCH:</b>                                     | A-23 heavy duty mast and yoke type. Fits Cat. II and III standard and quick Coupler. |
| <b>SHANKS:</b> | Heavy duty high clearance fabricated shanks that allow either staggered or opposed gang setting.                                                                                                                                                                             | <b>CYLINDERS:</b>                                 | Two 3 1/2" x 16" and all hoses for folding the tool bar. (3000 PSI)                  |
|                |                                                                                                                                                                                                                                                                              | <b>HOLD DOWN KIT &amp; SAFETY TRANSPORT LOCK:</b> | For 7 x 7 tool bar                                                                   |
|                |                                                                                                                                                                                                                                                                              | <b>PR. DEPTH GAUGE WHEELS:</b>                    | includes turnbuckle adjustment and 15 x 6 wheels.                                    |

**NOTE:** Scrapers and row markers are optional equipment and must be ordered separately.

| MODEL NO.                                                 | Description                                                                                     | Transport Width | Approximate Drawbar HP Required | Approximate Weight lbs (kg) | Suggested List Price             |
|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------|-----------------|---------------------------------|-----------------------------|----------------------------------|
| FHB6-5A                                                   | 6-Row 7" x 7" x 264" Tool Bar<br>Fits row spacing of 38" to 40"<br>DA-14-0036 Sweep Attachment  | 16'0"           | 100-135                         | 3557<br>396                 | \$ 11,312.00<br>1,300.00         |
| FHB8-6A                                                   | 8-Row 7" x 7" x 346" Tool Bar<br>Fits row spacing of 36" to 40"<br>DA-14-0037 Sweep Attachment  | 20'0"           | 130-180                         | 3896<br>528                 | <del>13,304.00</del><br>1,709.00 |
| FHB10-5A                                                  | 10-Row 7" x 7" x 346" Tool Bar<br>Fits row spacing of 33" to 40"<br>DA-14-0038 Sweep Attachment | 21'0"           | 140-200                         | 4447<br>660                 | 16,168.00<br>2,128.00            |
| FHB12-7A                                                  | 12-Row 7" x 7" x 424" Tool Bar<br>Fits row spacing 30" to 32"<br>DA-14-0039 Sweep Attachment    | 22'6"           | 180-250                         | 4997<br>792                 | 18,426.00<br>2,342.00            |
| <b>HYDRAULIC TOOL BAR CARRIERS</b>                        |                                                                                                 |                 |                                 |                             |                                  |
| HB6-5A                                                    | 6-Row Hydraulic Tool Bar Carrier<br>(Less Gangs and Gang Frames) with DW10 Gauge Wheels         | 16'0"           |                                 |                             | 4,871.00                         |
| HB8-6A                                                    | 8-Row Hydraulic Tool Bar Carrier<br>(Less Gangs and Gang Frames) with DW10 Gauge Wheels         | 20'0"           |                                 |                             | 5,172.00                         |
| <b>OPTIONAL EQUIPMENT</b>                                 |                                                                                                 |                 |                                 |                             |                                  |
| DA-01-0136                                                | Scrapers (Set of 4 for 2 Rows)                                                                  |                 |                                 | 14                          | Add 89.00                        |
| Note: See page 28 for optional blades in lieu of standard |                                                                                                 |                 |                                 |                             |                                  |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

# BEDDING HIPPER ASSEMBLIES

With Protect-O-Shield® Washers  
Featuring a 2-Year Bearing Warranty

25-5-5  
25-5-5+10  
(2004)

| Req'd | Part No.   | Description                                               | Total Weight | Suggested List Each |
|-------|------------|-----------------------------------------------------------|--------------|---------------------|
|       |            | <b>8-ROW 1-1/2" HEAVY DUTY</b>                            | <b>2586</b>  | <b>\$ 10,898.00</b> |
| 16    | DA-02-2314 | GANG ASSEMBLY 18" & 20" PLAIN BLADES                      |              |                     |
| 4     | DA-01-0111 | WEAR GUARDS (2-ROW SET)                                   |              |                     |
| (7)   | DA-01-0051 | DUAL GANG FRAME                                           |              |                     |
| 1     | DA-01-0052 | SHORT GANG FRAME                                          |              |                     |
| 1     | DA-01-0053 | LONG GANG FRAME                                           |              |                     |
| 1     | DA-01-0114 | BOX OF U-BOLTS & FASTENERS                                |              |                     |
| 4     | DA-01-0136 | SCRAPERS (SET OF 4 FOR 2 ROWS)                            |              |                     |
| 1     | DW-10      | PAIR GAUGE WHEELS                                         |              |                     |
|       |            | <b>10-ROW 1-1/2" HEAVY DUTY</b>                           | <b>3173</b>  | <b>13,380.00</b>    |
| 20    | DA-02-2314 | GANG ASSEMBLY 18" & 20" PLAIN BLADES                      |              |                     |
| 5     | DA-01-0111 | WEAR GUARDS (2-ROW SET)                                   |              |                     |
| 9     | DA-01-0051 | DUAL GANG FRAME                                           |              |                     |
| 1     | DA-01-0052 | SHORT GANG FRAME                                          |              |                     |
| 1     | DA-01-0053 | LONG GANG FRAME                                           |              |                     |
| 1     | DA-01-0115 | BUNDLE OF U-BOLTS & FASTENERS (2 BOXES)                   |              |                     |
| 5     | DA-01-0136 | SCRAPERS (SET OF 4 FOR 2 ROWS)                            |              |                     |
| 1     | DW-10      | PAIR GAUGE WHEELS                                         |              |                     |
|       |            | <b>12-ROW 1-1/2" HEAVY DUTY</b>                           | <b>3965</b>  | <b>16,709.00</b>    |
| 24    | DA-02-2314 | GANG ASSEMBLY 18" & 20" PLAIN BLADES                      |              |                     |
| 6     | DA-01-0111 | WEAR GUARDS (2-ROW SET)                                   |              |                     |
| (11)  | DA-01-0051 | DUAL GANG FRAME                                           |              |                     |
| 1     | DA-01-0052 | SHORT GANG FRAME                                          |              |                     |
| 1     | DA-01-0053 | LONG GANG FRAME                                           |              |                     |
| 1     | DA-01-0116 | BUNDLE OF U-BOLTS & FASTENERS (2 BOXES)                   |              |                     |
| 6     | DA-01-0136 | SCRAPERS (SET OF 4 FOR 2 ROWS)                            |              |                     |
| 2     | DW-10      | PAIR GAUGE WHEELS                                         |              |                     |
|       |            | Note: See page 28 for optional blades in lieu of standard |              |                     |

390 of list -

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE


**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

MANUFACTURING, INC.



# MISCELLANEOUS TOOL BAR AND HIPPER EQUIPMENT

**With Protect-O-Shield® Washers**  
**Featuring a 2-Year Bearing Warranty**  
**Only Available on 1-1/2" Square Gangs**

| MODEL NO.                                           | Description                                                                                                                    | Approximate Weight | Suggested List Price |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|--------------------|----------------------|
| <b>A-FRAMES</b>                                     |                                                                                                                                |                    |                      |
| A21M2                                               | Complete "A" Frame for use on 7" x 7" tool bar (Bdl. No. DE-01-0020)                                                           | 158                | \$ 590.00            |
| A-23                                                | Complete "A" Frame (hydraulic) for use on 7" x 7" tool bar (Bdl. No. DA-01-0096)                                               | 334                | 992.00               |
| A-24                                                | Complete "A" Frame for use on 4" or 7" tool bar. Accepts CatII or III three point hitch or quick coupler (Bdl. No. DE-01-0104) | 150                | 481.00               |
| <b>SINGLE BLADE GANGS</b>                           |                                                                                                                                |                    |                      |
| DA-02-2014                                          | WFP Gang with 22" x 1/4" (6mm) plain blades (1-1/2)Axle                                                                        | 76                 | 365.00               |
| DA-02-2114                                          | WFP Gang with 24" x 1/4" (6mm) plain blades (1-1/2)Axle                                                                        | 83                 | 371.00               |
| <b>HIPPER GANGS</b>                                 |                                                                                                                                |                    |                      |
| DA-02-3514                                          | Gang Assembly with 18" x 1/4" and 20" x 1/4" C.O. blades (1-1/2)Axle                                                           | 88                 | 448.00               |
| DA-02-2214                                          | Gang Assembly with 16" x 7 Ga. and 18" x 1/4" plain blades (1-1/2)Axle                                                         | 80                 | 399.00               |
| DA-02-2314                                          | Gang Assembly with 18" x 1/4" and 20" x 1/4" plain blades (1-1/2)Axle                                                          | 92                 | <del>435.00</del>    |
| DA-02-2414                                          | Gang Assembly with 20" x 1/4" and 22" x 1/4" plain blades (1-1/2)Axle                                                          | 102                | <del>470.00</del>    |
| DA-02-2714                                          | Gang Assembly with 20" x 1/4" and 22" x 1/4" C.O. blades (1-1/2)Axle                                                           | 99                 | <del>471.00</del>    |
| DA-02-2814                                          | Gang Assembly with 22" x 1/4" and 24" x 1/4" plain blades (1-1/2)Axle                                                          | 114                | <del>507.00</del>    |
| DA-02-2914                                          | Gang Assembly with 22" x 1/4" and 24" x 1/4" C.O. blades (1-1/2)Axle                                                           | 110                | 509.00               |
| DA-01-0136                                          | Scrapers (Set of 4 for 2 rows)                                                                                                 | 14                 | <del>89.00</del>     |
| DA-01-0111                                          | Wear Guard (Set = 2 Rows)                                                                                                      | 11                 | 40.00                |
| <b>INDIVIDUAL HIGH CLEARANCE HIPPER SHANKS</b>      |                                                                                                                                |                    |                      |
| (Gangs not included)                                |                                                                                                                                |                    |                      |
| DA-01-0051                                          | Combination Long and Short Gang Frame                                                                                          | 86                 | <del>265.00</del>    |
| DA-01-0052                                          | Fabricated Short Gang Frame                                                                                                    | 40                 | <del>128.00</del>    |
| DA-01-0053                                          | Fabricated Long Gang Frame                                                                                                     | 71                 | 181.00               |
| (Above Gang Frames for 4" x 7" or 7" x 7" Tool Bar) |                                                                                                                                |                    |                      |
| (U-Bolts and Fasteners must be ordered separately)  |                                                                                                                                |                    |                      |
| DA-01-0110                                          | Hold Down Kit for AMCO Hydraulic Hipers                                                                                        | 42                 | 152.00               |

AMCO PL Effective March 15, 2004

E.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE****MANUFACTURING, INC.****AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

*370*

## BEDDING HIPPER

### U-BOLTS AND WEAR GUARD BUNDLES

### OPTIONAL BLADE SIZES

#### Box of U-Bolts & 7/8" Locknuts for 1-1/2" Axle - 7 x 7 Tool Bar

| Stock No.  | Description               | Suggested List Each |
|------------|---------------------------|---------------------|
| DA-01-0139 | For expanding 2-Row ..... | \$ 93.94            |
| DA-01-0113 | 6-Row Unit .....          | 320.86              |
| DA-01-0114 | 8-Row Unit .....          | 411.00              |
| DA-01-0115 | 10-Row Unit .....         | 494.00              |
| DA-01-0116 | 12-Row Unit .....         | 579.00              |

Above boxes include u-bolts and 7/8" locknuts only for attaching gang frame to tool bar.

|            |                                                                           |       |
|------------|---------------------------------------------------------------------------|-------|
| DA-01-0111 | Wear Guards for expanding 2-Rows .....                                    | 40.00 |
| DA-01-0125 | FWFP (includes (1) L.H. & (1) R.H. Wear Guard, U-Bolts & Fasteners) ..... | 82.00 |

#### OPTIONAL BLADE SIZES

|                        |                                                |            |                |                 |
|------------------------|------------------------------------------------|------------|----------------|-----------------|
| <i>18" PL + 20" CO</i> | for 16" (7 Ga.) and 18" (1/4) Plain .....      | Ded        | per row        | \$ 32.00        |
|                        | for 18" (1/4) and 20" (1/4) Cutout .....       | Add        | per row        | \$ 12.00        |
|                        | <u>for 20" (1/4) and 22" (1/4) Plain .....</u> | <u>Add</u> | <u>per row</u> | <u>\$ 54.00</u> |
|                        | for 20" (1/4) and 22" (1/4) Cutout .....       | Add        | per row        | \$ 56.00        |
|                        | for 22" (1/4) and 22" (1/4) Cutout .....       | Add        | per row        | \$ 73.00        |
|                        | for 22" (1/4) and 24" (1/4) Plain .....        | Add        | per row        | \$ 90.00        |
|                        | for 22" (1/4) and 24" (1/4) Cutout .....       | Add        | per row        | \$ 90.00        |

*16" PL + 18" CO -*

*11.40*  
*55.00*  
*Deduct Deduct 36.00 = 432.00*

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE

**Amco**

MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# AMCO's Exclusive Ripper Hipper

xz2With Protect-O-Shield® Washers  
Featuring a 2-Year Bearing Warranty

## HEAVY DUTY - 1-1/2" SQUARE GANGS

### STANDARD SPECIFICATIONS

(Metrics in Parentheses)

**SUBSOILER TOOL BAR:** Heavy duty 7 x 7 x 5/8 wall tubing with two bars in center.

**HITCH:** Heavy Duty "A" Frame for Cat II and Cat. III three-point and quick coupler hitches

**SUBSOILER SHANKS:** 1" thick high strength T, steel parabolic shanks, 33" clearance

**SUBSOILER POINT:** Replaceable long, high carbon heat treated steel.

**PARALLELLINKAGES:** Heavy Duty with built-in parking pin-offs and hipper depth stop. Connects 7 x 7 to 7 x 4.

**BEDDING HIPPER TOOL BAR:** 7 x 4 tubing.

**BEDDING HIPPER GANGS:** 1-1/2" square axle with regreasable triple lip sealed ball bearings. One 22" (1/4"/6mm) and one 20" (1/4"/6mm) blade per gang. Three position angle adjustment.

**BEDDING HIPPER SHANKS:** Heavy Duty, high clearance shanks that allow either staggered or opposed gang setting.

**SHANK CLAMPS:** Heavy Duty 4 x 3 x 1/2 angle iron

Note: For Gauge Wheels, Parallel Bars, Scrapers, Mounts, etc., See page 30

### RIPPER & HIPPER COMPLETE

| MODEL NO. | Description                                                                                | Recommended Drawbar Horsepower* | Approximate Weight lbs | Suggested List Price |
|-----------|--------------------------------------------------------------------------------------------|---------------------------------|------------------------|----------------------|
| FRH4-3A   | Four Row Complete for 36" to 40" rows                                                      | 95-120                          | 2,875                  | \$ 8,478.00          |
| FRH6-3A   | Six Row Complete for 36" to 40" rows                                                       | 135-170                         | 4,152                  | 12,396.00            |
| FRH6-1A   | Six Row Narrow Skip Complete for 38" to 40/60" to 64" rows                                 | 135-170                         | 4,345                  | 12,944.00            |
| FRH6-2A   | Six Row 2 x 1 Skip or Narrow Skip on 8 row tool bar Complete for 38" to 40/60" to 80" rows | 135-170                         | 4,766                  | 13,308.00            |
| FRH8-3A   | Eight row Complete for 36" to 40" rows with 304" main frame                                | 175-220                         | 6,129                  | <u>16,660.00</u>     |
| FRH8-3B   | (Special) Eight Row Complete, with 356" main frame                                         | 175-220                         | 6,270                  | 16,802.00            |

\*Rated for comparing with Nebraska Tractor Test data and based on standard equipment at 12" to 13" subsoiler depth. Hipper at middle angle.

AMCO PL-Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**MANUFACTURING, INC.**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com



# RIPPER

## STANDARD SPECIFICATIONS

**SUBSOILER TOOL BAR:** Heavy duty 7 x 7 tubing with two bars in center.

**HITCH:** Heavy Duty "A" Frame for Cat. II and Cat. III three-point and quick coupler hitches.

**SUBSOILER SHANKS:** 1" thick high strength T, steel parabolic shanks, 33" clearance.

**SHANK CLAMPS:** Heavy Duty 4 x 3 x 1/2 angle iron

**SUBSOILER POINT:** Replaceable long, high carbon heat treated steel.

## RIPPER WITH 7x7 to 7x4 PARALLEL LINKAGE

| Model No. | Description                           | DBJP*   | Weight | Price       |
|-----------|---------------------------------------|---------|--------|-------------|
| R4-3      | 4 Shank Subsoiler (7 x 7 x 3/8 x 144) | 55-70   | 1436   | \$ 3,526.00 |
| R6-3      | 6 Shank Subsoiler (7 x 7 x 3/8 x 224) | 80-100  | 2028   | 5,036.00    |
| R6-2      | 6 Shank Subsoiler (7 x 7 x 3/8 x 272) | 80-100  | 2493   | 5,471.00    |
| R8-3      | 8 Shank Subsoiler (7 x 7 x 3/8 x 304) | 105-130 | 2936   | 6,660.00    |

\*Rated for comparing with Nebraska Tractor Test data and based on standard equipment at 12" to 13" subsoiler depth. Hippers at middle angle.

## OPTIONAL EQUIPMENT

| Model No     | Description                                                                                                                                                                                        | Approximate Weight | Suggested List Price |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------------------|
| DA-14-0011*  | Pt. DW-10 - Ripper Gauge Wheels (Recommended for 6 and 8 Row Models)                                                                                                                               | 204                | \$ 847.00            |
| DA-14-0044** | Pt. DW-13 - Ripper Gauge Wheels (7 x 4)                                                                                                                                                            | 213                | 1,002.00             |
| DA-14-0043** | Pt. DW-12 - Ripper Gauge Wheels (7 x 7)                                                                                                                                                            | 208                | 1,005.00             |
| DB 01-0023   | Parking Stand (Recommended for Ripper)<br>Parallel Linkage - 7 x 7 to 7 x 7 tube in lieu of standard.<br>Two (2) required for 4 row; three (3) required for 6 row;<br>Four (4) required for 8 row. | 24                 | 55.20                |
| DB 01-0018   | Parallel Linkage - 7 x 7 to 7 x 7 bar                                                                                                                                                              | 1 ea               | N/C                  |
| DB 01-0017   | Parallel Linkage - 7 x 7 to 7 x 4 bar                                                                                                                                                              | 150 ea             | 389.00               |
| DA 01-0136   | Scrapers (Set of 4 for 2 rows)                                                                                                                                                                     | 149 ea             | 389.00               |
| DB 01-0020   | Shank and Mount - 7 x 7                                                                                                                                                                            | 14                 | 89.00                |
|              | *Recommended for 6 row and 8 row models                                                                                                                                                            | 147                | 414.00               |
|              | **20.5 x 8.00 Tire and 10" wheel included                                                                                                                                                          |                    |                      |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

**MANUFACTURING, INC.**

# HYDRAULIC ROW MARKER

## STANDARD SPECIFICATIONS

**BEARING:** Triple lip sealed ball type

**DISC:** 2 - 16" blades

**HYDRAULIC CYLINDERS:** 2 - 2" x 8" for hydraulic operation

**ADJUSTABLE SPACING:** 72" x 122"

4 - 40" rows      6 - 30" rows

6 - 40" rows      8 - 30" rows

**ANGLE ADJUSTMENT:** Blade angle is adjustable for different soil types. Blade can be reversed for light soil

| MODEL NO. | Nn. of Discs | Disc Size & Type                                                                                                 | Approximate Weight | Suggested List Price |
|-----------|--------------|------------------------------------------------------------------------------------------------------------------|--------------------|----------------------|
| 4-6H3     | 2            | 16" Plain<br><b>ADAPTER KITS</b><br>(Must be ordered with each Row Marker)                                       | 270                | \$ 1,193.00          |
| M-25      |              | Kit for 2-1/2" x 2-1/2" Bar     | 13                 | 62.00                |
| M-47      |              | Kit for 4" x 7" or 5" x 7" Bar  | 13                 | 54.00                |
| M 77      |              | Kit for 7" x 7" Bar             | 14                 | 88.00                |

## AMCO's Exclusive Water Furrow Plow

With Protect-O-Shield® Washers  
Featuring a 2-Year Bearing Warranty

## RIGID HEAVY DUTY - 1-1/2" SQUARE GANGS

### STANDARD SPECIFICATIONS

**AXLES:** 1-1/2" Square

**BLADES:** 22" x 1/4 Gauge Plain

**SHANKS:** (2) Fabricated Short Gang Frame

**BEARINGS:** 1-1/2" Sq. Bore Regreassable Triple Lip Seal

**TOOL BAR AND HITCH:** 4x7x110" long. A-24 A-Frame accepts Cat. II or III Three Point Hitch or Quick Coupler

| MODEL NO.                 | Nn. of Discs | Disc Size & Type                                                    | Approximate Drawbar Required | Approximate Weight | Suggested List Price  |
|---------------------------|--------------|---------------------------------------------------------------------|------------------------------|--------------------|-----------------------|
| FWFPA                     | 1-1/2      2 | 22" Plain (1/4)                                                     | 30 - 60                      | 626                | \$ 1,518.00           |
| <b>OPTIONAL EQUIPMENT</b> |              |                                                                     |                              |                    |                       |
| DA-01-0099                |              | Parking Stand<br>For 24" Plain Blades, 1-1/2 sq. Axle, add per unit |                              | 34<br>Add 14       | Add 95.00<br>Add 7.00 |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

**SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE**



MANUFACTURING, INC.

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

# BEDDING HIPPER ASSEMBLIES

With Protect-O-Shield® Washers  
Featuring a 2-Year Bearing Warranty

For in-house use only

| Qty'd                                                     | Part No.   | Description                             | 2004<br>Cost ea. | Total<br>Weight | EA     | Suggested<br>List Each | EXT'D            |
|-----------------------------------------------------------|------------|-----------------------------------------|------------------|-----------------|--------|------------------------|------------------|
| <b>8-ROW 1-1/2" HEAVY DUTY</b>                            |            |                                         |                  | <b>2586</b>     |        | <b>\$ 10,898.00</b>    |                  |
| 16                                                        | DA-02-2314 | GANG ASSEMBLY 18" & 20" PLAIN BLADES    | 139.77           | 92 ea           | 435    | 6,960.00               |                  |
| 4                                                         | DA-01-0111 | WEAR GUARDS (2-ROW SET)                 | 12.06            | 10              | 40     | 160.00                 |                  |
| 7                                                         | DA-01-0051 | DUAL GANG FRAME                         | 46.98            | 88              | 265    | 1,855.00               |                  |
| 1                                                         | DA-01-0052 | SHORT GANG FRAME                        | 48.33            | 40              | 128    | 128.00                 |                  |
| 1                                                         | DA-01-0053 | LONG GANG FRAME                         | 66.18            | 71              | 181    | 181.00                 |                  |
| 1                                                         | DA-01-0114 | BOX OF U-BOLTS & FASTENERS              | 129.89           | 87              | 411    | 411.00                 |                  |
| 4                                                         | DA-01-0136 | SCRAPERS (SET OF 4 FOR 2 ROWS)          | 35.53            | 14              | 89     | 356.00                 |                  |
| 1                                                         | DW-10      | PAIR GAUGE WHEELS                       | 333.93           | 204             | 847.00 | 847.00                 |                  |
|                                                           |            |                                         | <u>3703.87</u>   | 2586            |        |                        | <u>10,898.00</u> |
| <b>10-ROW 1-1/2" HEAVY DUTY</b>                           |            |                                         |                  | <b>3173</b>     |        | <b>13,380.00</b>       |                  |
| 20                                                        | DA-02-2314 | GANG ASSEMBLY 18" & 20" PLAIN BLADES    | 10               | 92              | 435    | 8700.00                |                  |
| 5                                                         | DA-01-0111 | WEAR GUARDS (2-ROW SET)                 |                  | 10              | 40     | 200.00                 |                  |
| 9                                                         | DA-01-0051 | DUAL GANG FRAME                         |                  | 88              | 265    | 2385.00                |                  |
| 1                                                         | DA-01-0052 | SHORT GANG FRAME                        |                  | 40              | 128    | 128.00                 |                  |
| 1                                                         | DA-01-0053 | LONG GANG FRAME                         |                  | 71              | 181    | 181.00                 |                  |
| 1                                                         | DA-01-0115 | BUNDLE OF U-BOLTS & FASTENERS (2 BOXES) | 157.65           | 106             | 494    | 494.00                 |                  |
| 5                                                         | DA-01-0136 | SCRAPERS (SET OF 4 FOR 2 ROWS)          |                  | 14              | 89     | 445.00                 |                  |
| 1                                                         | DW-10      | PAIR GAUGE WHEELS                       |                  | 204             | 847.00 | 847.00                 |                  |
|                                                           |            |                                         | <u>4537.26</u>   | 3173            |        |                        | <u>13,380.00</u> |
| <b>12-ROW 1-1/2" HEAVY DUTY</b>                           |            |                                         |                  | <b>3965</b>     |        | <b>16,709.00</b>       |                  |
| 24                                                        | DA-02-2314 | GANG ASSEMBLY 18" & 20" PLAIN BLADES    |                  | 92              | 435    | 10,440.00              |                  |
| 6                                                         | DA-01-0111 | WEAR GUARDS (2-ROW SET)                 |                  | 10              | 40     | 240.00                 |                  |
| 11                                                        | DA-01-0051 | DUAL GANG FRAME                         |                  | 88              | 265    | 2,915.00               |                  |
| 1                                                         | DA-01-0052 | SHORT GANG FRAME                        |                  | 40              | 128    | 128.00                 |                  |
| 1                                                         | DA-01-0053 | LONG GANG FRAME                         |                  | 71              | 181    | 181.00                 |                  |
| 1                                                         | DA-01-0116 | BUNDLE OF U-BOLTS & FASTENERS (2 BOXES) | 135.91           | 126             | 579    | 579.00                 |                  |
| 6                                                         | DA-01-0136 | SCRAPERS (SET OF 4 FOR 2 ROWS)          |                  | 14              | 89     | 534.00                 |                  |
| 2                                                         | DW-10      | PAIR GAUGE WHEELS                       |                  | 204             | 847.00 | 1694.00                |                  |
|                                                           |            |                                         | <u>5704.58</u>   | 3965            |        |                        | <u>16,709.00</u> |
| Note: See page 28 for optional blades in lieu of standard |            |                                         |                  |                 |        |                        |                  |

AMCO PL Effective March 15, 2004

F.O.B. Yazoo City, Mississippi

SPECIFICATIONS AND PRICES SUBJECT TO CHANGE WITHOUT NOTICE

**Amco**

**AMCO Manufacturing, Inc.**

P. O. Box 1107, 800 South Industrial Parkway, Yazoo City, MS 39194, USA

(800) 748-9022 (662) 746-4464 Fax (662) 746-6825

www.amcomfg.com

MANUFACTURING, INC.