



Selling points for all models of AMCO Levee Plows



- **LF6 and MLF6 – 9” blade spacing**
 - **LJ6 and MLJ6 – 10½” blade spacing**
- AMCO-exclusive Follow-the-Levee feature that allows gangs to shift independently from the tractor to follow sharply curving levee lines.
 - Available in 8-blade, 10-blade, and 12-blade models. (Shown above is an 8-blade model)
 - AMCO Protect-O-Shield® bearings feature an exclusive protective shield to protect its triple seals. Our bearing prevents blown seals and prevents wrap damage.
 - AMCO Protect-O-Shield® bearings are guaranteed for 2 full years.
 - A main frame 7” x 4” x 3/8” toolbar and 1½” **square, high-carbon, cold-rolled steel axles.**
 - Gang angles that are easily adjustable with pins from 18 to 28 degrees.
 - A hitch designed to accommodate category II and III hitches for quick couplers and conventional 3-point hitches.
 - Adjustable, telescoping frames to accommodate narrow or wide-based levees.
 - A 3” x 8” hydraulic cylinder on each gang to adjust gang tilt from tractor cab (LF6 and LJ6 only)
 - 3/16” x 6½” x 8”, high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2½” x 2½” square tubing. The scrapers are attached to the 2½” x ½” thick arms with heavy-duty u-bolts
 - Standard 24” x 1/4” blades with a 10” backup blade on the end blade of each gang.
 - Standard heavy-duty ductile iron bearing risers, wear guards, and zerk guards

- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.

AMCO Exclusive Product Performance Guarantee – Repair, Replace, or Refund: AMCO Guarantees Performance – The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

Optional equipment:

- manual control ratchet jacks
- 24" x 1/4" cutout blades
- 26" x 1/4" cutout blades
- 26" x 1/4" plain blades
- feathering blade set (2) with backup blade

Protect-O-Shield® bearings

