



MANUFACTURING, INC.



Selling points for AMCO's Wicked Warrior Tandem Lift Disc



- Available in 4', 5', 6', and 8' cutting widths
- Designed for 30 to 55 Horsepower tractors
- 1-1/8" square, high carbon, cold rolled steel axles
- 18" x 3/16" standard cutout blades
- Main frame: 2" x 3" square tubing with 3" x 3" cross braces 3/16" thick
- Gang frames: 3" x 3" square tubing 1/4" thick
- Pin-adjustable gang angle to offer aggressive tillage or soil finishing options
- Category 1 quick-hitch compatible
- Welded 7 1/2" blade spacer spools
- Powder-coated finish for enhanced durability
- Heavy-duty reinforced bearing risers with extra bracing for better gang support
- Eight heavy-duty bearings with two-year warranty: 1-1/8" round bore, greaseable, triple-ball type with zerk guards
- The ability to easily add fresh grease to bearings helps ensure long-term dependability and protects from damage

AMCO Exclusive Product Performance Guarantee – Repair, Replace, or Refund: AMCO Guarantees Performance – The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

Optional Equipment: 18" x 3/16" Plain blades

Wicked Warrior Models (available in AMCO yellow or Ag green)

Model	Cutting Width	No. of Discs	Approx. Engine HP Required	Approx. Weight lbs*
WW-1218	4'	12	28	420
WW-1618	5'	16	35	742
WW-2018	6'	20	45	825
WW-2418	8'	24	55	1,290

** To calculate weight per blade on each unit, divide the approximate weight by the number of blades. Specifications for all models subject to change without notice.*