



## Selling Points - AMCO F17 *Double Offset Tandem Disc Harrow* (Non-folding)



### ***F17 features:***

- Available in 9'3" to 16'6" cutting widths
- 9" blade spacing
- Adjustable gang angle 18° to 22° on front gangs, and 17° to 21° on rear gangs
- Standard 22"x1/4" Plain blades with diminishing leveling blades
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1.5" square, high carbon cold rolled steel axles
- AMCO **Protect-O-Shield® bearings** feature an exclusive protective shield to protect its triple seals. Our bearing prevents blown seals and prevents wrap damage.
- AMCO **Protect-O-Shield® bearings** are guaranteed for 2 full years.
- Main frames featured boxed, all-welded steel tubing
- 70" tongue with reversible clevis
- Standard light kit, safety chains, & SMV emblem

- Front to rear leveling spring allows easy adjustment in the field
- Standard gang bolt wrench and a 4"x8" (3,000 PSI)hydraulic cylinder with hoses to tractor
- Standard heavy-duty ductile iron bearing risers, wear guards, and zerk guards
- Wear guards to protect bearing housings and zerk guards to protect grease fittings
- Two 15x8" wheels with heavy duty 6-bolt hubs on 9'3", 10'6", & 12'0".
- Four 15x8" wheels with heavy duty 6-bolt hubs on 13'6", 15'0", & 16'6".
- Outrigger bars and clamps also standard on 13'6", 15'0", & 16'6" models.
- $\frac{3}{16}$ " x 6 $\frac{1}{2}$ " x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2 $\frac{1}{2}$ " x 2 $\frac{1}{2}$ " square tubing. The scrapers are attached to the 2 $\frac{1}{2}$ " x  $\frac{1}{2}$ " thick arms with heavy-duty u-bolts

**AMCO Exclusive Product Performance Guarantee** – Repair, Replace, or Refund: AMCO Guarantees Performance – The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

**Optional Equipment:**

- Feathering blade with scraper for rear gangs
- Shock absorber gang risers
- 22"x1/4" cutout blades, 24"x1/4" plain and cutout blades
- 15"x10" wheels in place of 15"x8" wheels
- Dual wheels in place of single wheels (9.5L or 11L tires)

**F17 Double Offset Tandem Disc Harrow models**

Model	Cutting Width	No. of Discs	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs.*
<b>F17-2622</b>	9'3"	26	8	68–101	3,414
<b>F17-3022</b>	10'6"	30	8	81–108	3,698
<b>F17-3422</b>	12'0"	34	8	95–122	3,982
<b>F17-3822**</b>	13'6"	38	12	108–135	4,816
<b>F17-4222**</b>	15'0"	42	12	122–155	5,130
<b>F17-4622**</b>	16'6"	46	12	142–176	5,644

\*To calculate weight per blade on each unit, divide the approximate weight by the number of blades.

\*\*Includes 2 outrigger bars and clamps.