



## Selling Points - AMCO F41/J41 *Wheel Offset Harrows*



### **F41**

9" blade spacing

### **J41**

10 1/2" blade spacing

### ***F41 & J41 features:***

- 4"x4"x1/4" all welded main frame. 44" wide.
- Two 9.5L tires mounted on 15x6" wheels with 6-bolt hubs
- Adjustable gang angle 17° to 23° front to rear
- Standard 22"x1/4" Plain blades on **F41**, and 24"x1/4" Cut out blades on **J41**
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1.5" square axles
- AMCO **Protect-O-Shield® bearings** feature an exclusive protective shield to protect its triple seals. Our bearing prevents blown seals and prevents wrap damage.
- AMCO **Protect-O-Shield® bearings** are guaranteed for 2 full years.
- Spring loaded leveling system with turnbuckle for adjustment front to rear.
- Five tongue position adjustments for both left and right offset positions.
- Standard light kit, safety chains, & SMV emblem
- 4"x8" (3,000 PSI) hydraulic cylinder with stroke control for cutting depth adjustment. Includes hose bundle to tractor.

- Standard heavy-duty ductile iron bearing risers, wear guards, and zerk guards
- HD high carbon steel replaceable scraper blades on ½"x1½" shanks, mounted on 2"x2"x3/8" angle iron bars.

**AMCO Exclusive Product Performance Guarantee** – Repair, Replace, or Refund: AMCO Guarantees Performance – The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

#### Optional Equipment:

- Feathering blade with scraper for rear gang
- Shock absorber bearing risers
- Optional blade sizes available
  - 22"x1/4" Cut out *or* Plain blades
  - 24"x1/4" Cutout *or* Plain blades

### F41 & J41 Wheel Offset Harrow Models

Model	Cutting Width	No. of Discs	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs*
<b>F41 Model</b>					
<b>F41-1822</b>	6'9"	18	6	68-88	2,428
<b>F41-2022</b>	7'6"	20	6	75-95	2,568
<b>F41-2222</b>	8'3"	22	8	81-101	2,801
<b>F41-2422</b>	9'0"	24	8	88-108	2,922
<b>F41-2622</b>	9'9"	26	8	95-115	3,036
<b>F41-2822</b>	10'6"	28	8	101-122	3,257
<b>J41 Model</b>					
<b>J41-1624</b>	7'0"	16	6	68-88	2,592
<b>J41-1824</b>	7'10"	18	6	74-95	2,739
<b>J41-2024</b>	8'8"	20	6	81-101	2,905
<b>J41-2224</b>	9'6"	22	8	88-108	3,154
<b>J41-2424</b>	10'4"	24	8	95-115	3,345

*\*To calculate weight/blade, divide the approximate weight of the model by the number of disc blades.*