

The AMCO logo is a yellow rectangular box with the word "AMCO" in black, bold, sans-serif capital letters inside.

Introducing AMCO's F15 100% Tillage



AMCO F15 Double Offset Tandem Harrow:

- Double Offset Tandem design overlapping front discs without the need for a center shank to level off the center.
- Folding Flexwings to follow the contour of the field.
- 9" blade spacing
- Standard 24"x¼" Plain blades
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1.5" square axles
- AMCO Protect-O-Shield Bearings feature an exclusive protective shield to protect its triple seals. Our bearing prevents blown seals and prevents wrap damage.
- Mainframes featured boxed, all-welded steel tubing
- 17-degree gang angle. No adjustment necessary
- Standard light kit, safety chains, & SMV emblem
- DIAL-A-DEPTH control ensures an even cutting depth
- Front Depth Gauge Wheels to assist with a controlled depth of the wings.
- Standard heavy-duty ductile iron bearing risers, wear guards, zerk guards, and bearings are guaranteed for 2 full years.
- ¾" x 6½" x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2½" x 2½" square tubing. The scrapers are attached to the 2½" x ½" thick arms with heavy-duty u-bolts



The best tillage tools deserve the best guarantee.



If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

800.748.9022



AMCOmfg.com