

The AMCO logo is displayed in a yellow rectangular box with a black border, centered at the top of the page. The background of the top section is a photograph of a dark brown, tilled agricultural field under a clear sky.

**Rely on AMCO's F17 for dependable seedbed preparation**

## **AMCO's Double Offset Tandem Disc Harrow**



### **F17 Double Offset Tandem Disc Harrow features include:**

- Eight or twelve (depending on model size) greaseable ball-type, toggle-mounted Protect-O-Shield® Bearings, guaranteed for two full years
- 1½" square, high-carbon, cold-rolled steel axles
- Reversible clevis
- ¾" x 6½" x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2½" x 2½" square tubing. The scrapers are attached to the 2½" x ½" thick arms with heavy-duty U-bolts
- Standard 22" x ¼" plain blades on 9" spacing
- Diminishing blades with 16" feathering blades on the rear gang
- Standard gang bolt wrench and a 4" x 8" (3,000 PSI) hydraulic cylinder with hoses to tractor
- Wear guards to protect bearing housing and zerk guards to protect grease fitting
- Dealing with unexpected or unpredictable terrain? Try the optional Shock Absorber Gang Riser, which allows the gang on the harrow to move upward and back to relieve shock when the disc blades encounter an obstacle in the ground
- Safety features include safety chains, slow-moving placard, and light kits



### **The best tillage tools deserve the best guarantee.**

If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

