



AMCO

## AMCO's F42, J42, J43, J44 series



F42  
9" blade spacing

J42, J43, J44  
10 1/2" blade spacing

### F42 & J42 features:

- Available in small (50") and large (86") mainframe.
- Adjustable gang angle 17° to 25° front to rear.
- Standard 24"x1/4" Plain blades with diminishing leveling blades.
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1.5" square axles.
- AMCO Protect-O-Shield® bearings feature an exclusive protective shield to protect its triple seals. Our bearing prevents blown seals and prevents wrap damage.
- Positive screw-type depth control for maintaining set cutting depth.
- Adjustable 88 1/2" tongue with base hitch and tongue jack.
- Heavy-duty 3,000 PSI hydraulic cylinders to adjust cutting depth and raise the disc for transport.
- Standard heavy-duty ductile iron bearing risers, wear guards, and zerk guards.
- 3/16" x 6 1/2" x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2 1/2" x 2 1/2" square tubing. The scrapers are attached to the 2 1/2" x 1/2" thick arms with heavy-duty u-bolts.

### J43 & J44 features:

AMCO's extra-heavy-duty Wheel Offset Harrow models have the same features as the F42, J42, as well as:

- Standard Shock Absorber Gang Risers to help prevent damage from rocks and stumps..
- Larger bearings.
- All J44 models have split gangs, and back up discs behind each blade for reinforcement.

### Optional Equipment:

- Feathering blade with scraper for rear gang.
- Shock absorber gang risers on F42 & J42.
- Optional blade available sizes up to 28"x5/16" cutout or smooth.



The best tillage tools deserve the best guarantee.



If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

800.748.9022



AMCOmfg.com