

The AMCO logo is centered within a yellow rectangular border at the top of the page. Above the logo is a photograph of a plowed field with dark brown soil and a line of trees in the distance.

## AMCO's J41/ F41 Wheel Offset Harrow



- 4"x4"x1/4" all welded main frame. 44" wide.
- Two 9.5L tires mounted on 15"x6" wheels with 6-bolt hubs.
- Adjustable gang angle 17° to 23° front to rear
- Standard 22"x1/4" Plain blades on F41, and 24"x1/4" cut out blades on J41.
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1 1/2" square axles
- AMCO Protect-O-Shield<sup>®</sup> bearings feature an exclusive protective shield to protect its triple seals. Our bearing prevents blown seals and prevents wrap damage.
- Spring loaded leveling system with turnbuckle for adjustment front to rear.
- Standard light kit, safety chains, & SMV emblem
- 4"x8" (3,000 PSI) hydraulic cylinder with stroke control for cutting depth adjustment. Includes hose bundle to tractor.
- Standard heavy-duty ductile iron bearing risers, wear guards, and zerk guards
- HD high carbon steel replaceable scraper blades on 1/2"x1 1/2" shanks, mounted on 2"x2"x3/8" angle iron bars.



The Best Tillage Tools deserve the best guarantee.



If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

800.748.9022



AMCOmfg.com