



AMCO

AMCO's Light Duty D41 Wheel Offset Harrow



- Designed for use with 34 to 95 horsepower tractors.
- 4" x 3" x 1/4" all welded main frame, 43" wide.
- 4" x 3" x 1/4" gang frames.
- Two 9 1/2L tires mounted on to 15" x 6" wheels with 6 bolt hubs .
- Adjustable gang angle 17° to 23° front to rear.
- 9" Blade spacing.
- Standard 22" x 3/16" plain blades with diminishing leveling blades.
- 1 1/8" square axles.
- Regreasable triple sealed bearings with two year warranty: 1 1/8" round bore.
- Spring loaded leveling system with turn buckle for adjustment front to rear.
- Adjustable tongue with five adjustments for both left and right offset positions.
- Standard light kit, safety chains, & SMV emblem.
- 3" x 8" x 1 1/4" hydraulic cylinder with stroke control for cutting depth adjustment.
- Standard heavy duty ductile iron bearing risers.
- HD high carbon steel replaceable scraper blades on 1/2" x 1 1/2" shanks, mounted on 2" x 2" x 3/8" angle iron bars.



The Best Tillage Tools deserve the best guarantee.



If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

800.748.9022



AMCOmfg.com