



J42B - Wheel Offset Harrow

- Large (86") mainframe.
- Dual wheels for improved flotation.
- Adjustable gang angle 17° to 25° front to rear.
- Standard 24"x1/4" Plain blades with diminishing leveling blades.
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1.5" square axles.
- Disc gangs are equipped with maintenance free bearings that are sealed to eliminate the possibility of contamination and need for re-lubrication.
- Bearings come with a 3 year warranty.
- Main frames featured boxed, all-welded steel tubing.
- Positive screw-type depth control for maintaining set cutting depth.
- Standard light kit, safety chains, & SMV emblem.
- Adjustable 88½" tongue with base hitch and tongue jack.
- Heavy-duty 3,000 PSI hydraulic cylinders to adjust cutting depth and raise the disc for transport.
- 3/16" x 6½" x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2½" x 2½" square tubing. The scrapers are attached to the 2½" x ½" thick arms with heavy-duty u-bolts.



The Best Tillage Tools deserve the best guarantee.



If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.