



## Bedding Hipper/ Toolbars



### Features:

- Hipper feature 11'2" square axles with Protect-O-Shield bearings to eliminate blown seals and prevent wrap damage.
- Backed by AMCO's exclusive Two-Year Warranty each housing features two bearings for added durability.
- Perform in high-residue conditions and offer trouble-free seedbed preparation.
- Choose from three Heavy-Duty Toolbar options: hydraulic flat-folding dual toolbar, hydraulic 90o folding single toolbar, or rigid single toolbar.
- Folding toolbars are designed for easy transport and storage.
- Adjustable gangs offer three positions to achieve desired seedbed height.
- Heavy-Duty, high-clearance fabricated gang frames can be staggered for extreme residue conditions or opposed for normal operation.
- All welded gang frames attach to toolbar with two 7/8" heat-treated u-bolts.
- Standard 18" and 20" Plain or Cutout blades 1'4" thick.
- Standard gauge wheels with ratcheting turnbuckle to achieve desired operating depth.
- Heavy-duty replaceable adjustable scrapers with u-bolt.

### Toolbar Models

Type	Cutting Width	Transport Width	Description	Rows & Spacing
Rigid single toolbar	280"	23'4"	single toolbar, 7" x 7" x 1/4"; heavy-duty rigid, non-folding	fits row spacing of 36"-40" for 6-row or 30"-32" for 8-row
Rigid single toolbar	344"	28'8"	single toolbar, 7" x 7" x 1/2"; heavy-duty rigid, non-folding	fits row spacing of 38"-40" for 6-row or 36"-42" for 8-row
Hydraulic folding single toolbar	264"	16'	single toolbar, 7" x 7" x 1/4"; heavy-duty hydraulic, vertical folding	fits row spacing of 38"-40" for 6-row
Hydraulic folding single toolbar	346"	20'	single toolbar, 7" x 7" x 1/2"; heavy-duty hydraulic, vertical folding	fits row spacing of 36", 40", and 42" for 8-row
Hydraulic folding dual toolbar	367"	16'	dual toolbar, 7" x 7" x 1/4"; heavy-duty hydraulic, flat folding	fits row spacing of 30" for 12-row or 30"-36" for 10-row
Hydraulic folding dual toolbar	497"	22'	dual toolbar, 7" x 7" x 1/4"; heavy-duty hydraulic, flat folding	fits row spacing of 36"-40" for 10- or 12-row, 30" for 16-row

### Bedding Hipper Assemblies

Blade Configuration	Blade Options
Single Blade	Cutout or smooth blades. 16", 18", 20", 22", or 24"
Double Blade	Cutout or smooth blades. 16" & 18", 18" & 20", 20" & 22", or 22" & 24"

### The Best Tillage Tools deserve the Best Guarantee

If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back

