



# F15 Double Offset Tandem Harrow



## Features:

- Double Offset Tandem design – overlapping front discs without the need for a center shank to level off the center.
- Folding Flexwings to follow the contour of the field.
- 9" blade spacing.
- Standard 24"x1/4" Plain blades.
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1.5" square axles.
- Main frames featured boxed, all-welded steel tubing.
- 17 degree gang angle. No adjustment necessary.
- Standard light kit, safety chains, & SMV emblem.
- DIAL-A-DEPTH control ensures an even cutting depth.
- Front Depth Gauge Wheels to assist with controlled depth of the wings.
- Standard heavy-duty ductile iron bearing risers and wear guards.
- 3/16" x 6 1/2" x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2 1/2" x 2 1/2" square tubing. The scrapers are attached to the 2 1/2" x 1/2" thick arms with heavy-duty u-bolts.

## F15B Workhorse

Model	Cutting Width	Transport Width	Transport Height	No. of Disc Blades	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs*
F15B-4822	18'8"	12'6"	9'6"	46	18	155-176	6,705
F15B-6022	18'0"	12'6"	10'3"	50	18	182-189	7,419
F15B-5422	19'6"	12'6"	11'0"	54	18	189-203	7,693
F15B-5822	21'0"	12'6"	11'9"	58	18	182-223	8,348
F15B-6622	24'0"	12'6"	12'6"	66	20	202-243	9,306

## F15 Heavy Duty

Model	Cutting Width	Transport Width	Transport Height	No. of Disc Blades	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs*
F15-6624	24'0"	14'6"	11'0"	66	20	243-297	11,991
F15-7424	27'0"	14'6"	12'	74	22	243-297	12,283
F15-8224	30'0"	14'6"	13'3"	82	22	256-316	12,935

NOTE: 15 x 10 8-hole wheels and 8-hole hubs optional equipment on F15-66 blade, 74 blade, and 82 blade (center section only).

## F15 Giant

Model	Cutting Width	Transport Width	Transport Height	No. of Disc Blades	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs*
F15-9424	34'8"	17'8"	14'0"	94	28	310-376	15,423
F15-10624	39'0"	17'8"	15'9"	106	30	337-405	16,671

NOTE: 15 x 10 8-hole wheels and 8-hole hubs standard equipment on F15-94 blade and 106 blade (center section only).

## The Best Tillage Tools deserve the Best Guarantee

If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back

