



## F17 Double Offset Tandem Disc Harrow



- Available in 9'3" to 16'6" cutting widths
- 9" blade spacing.
- Adjustable gang angle 18° to 22° on front gangs, and 17° to 21° on rear gangs.
- Standard 22"x4" Plain blades with diminishing leveling blades.
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1.5" square, high carbon cold rolled steel axles.
- 70" tongue with reversible clevis.
- Standard light kit, safety chains, & SMV emblem bearings are guaranteed for 2 full years.
- Front to rear leveling spring allows easy adjustment in the field.
- Standard gang bolt wrench and a 4"x8" (3,000 PSI) hydraulic cylinder with hoses to tractor.
- Standard heavy-duty ductile iron bearing risers, wear guards
- Wear guards to protect bearing housings.
- Two 15x8" wheels with heavy duty 6-bolt hubs on 9'3", 10'6", & 12'0".
- Four 15x8" wheels with heavy duty 6-bolt hubs on 13'6", 15'0", & 16'6".
- Outrigger bars and clamps also standard on 13'6", 15'0", & 16'6" models.
- 3/16" x 6 1/2" x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2 1/2" x 2 1/2" square tubing. The scrapers are attached to the 2 1/2" x 1/2" thick arms with heavy-duty u-bolts.
- AMCO's PEER Maintenance Free gang bearing. No need for daily relube.

### F17 Double Offset Tandem Disc Harrow models

Model	Cutting Width	No. of Discs	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs.*
F17-2622	9'3"	26	8	68-101	3,414
F17-3022	10'6"	30	8	81-108	3,698
F17-3422	12'0"	34	8	95-122	3,982
F17-3822**	13'6"	38	12	108-135	4,816
F17-4222**	15'0"	42	12	122-155	5,130
F17-4622**	16'6"	46	12	142-176	5,644

*\*To calculate weight per blade on each unit, divide the approximate weight by the number of blades.*

*\*\*Includes 2 outrigger bars and clamps.*

## The Best Tillage Tools deserve the Best Guarantee

If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back

800.748.9022



AMCOmfg.com