



Down-to-Earth Advantages of AMCO's LOF: Lift Offset Harrow

LOF features:

- Available in 7'6", 8'3", and 9'0" cutting widths.
- 9" blade spacing.
- Adjustable gang angle 14° to 18° front to rear to adapt to any soil conditions.
- Standard 24"x1/4" Cut-out blades with right front and right rear blades stepped down 2" less.
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1.5" square, high carbon cold rolled steel axles.
- AMCO's PEER® Maintenance Free gang bearing - no need for daily relube.
- Main frames featured boxed, all-welded steel tubing 3"x4"x1/4".
- 3"x5"x1/4" rectangular tubing on gang frames.
- Heavy-duty 3-point hitch with reversible 1-7/16" lower hitch pin fits CAT II and III hitches and is quick-hitch compatible.
- Spring loaded leveling system.
- Standard heavy-duty ductile iron bearing risers, wear guards, and zerk guards.
- Wear guards to protect bearing housings, and zerk guards to protect grease fittings
- HD high carbon steel scraper blades on 1/2"x1 1/2" shanks, mounted on 2"x2"x3/8" angle iron bars.

LOF Lift Offset Harrow Models

Model	Cutting Width	No. of Discs	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs.*
LOF-2024	7'6"	20	8	61	2,152
LOF-2224	8'3"	22	8	68	2,272
LOF-2424	9'0"	24	8	68	2,392

*To calculate weight per blade on each unit, divide the approximate weight by the number of blades.
Specifications for all models subject to change without notice

The Best Tillage Tools deserve the best guarantee.

If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.