

The AMCO logo is displayed in a yellow rectangular box with a black border. The letters 'AMCO' are in a bold, black, sans-serif font.

**The small disc that can still pack a big punch!**

## **AMCO's LTF Lift Double Offset Harrow**



- Gangs are double offset for 100% tillage. Eliminates the need for a center sweep.
- 1½" axles and bearings are identical to those in the AMCO 39' disc harrow, ensuring the harrow is bulletproof.
- Welded steel spacers to prevent breakage upon impact with solid obstacles such as rocks.
- Small-frame for 32 to 52 engine horsepower: Large-frame for 60 to 110 engine horsepower.
- Gang angles are adjustable from 14-18 degrees.
- Small-frame models Cat 1. Large-frame models Cat 2 & 3. Both frame sizes are quick hitch compatible.
- Small-frame models 18" cut-outs large-frame models 22" cut-outs.
- Shock absorbing bearing risers to relieve shock when the disc blades encounter an obstacle in the ground.
- Frames are powder coated for a durable, long-lasting finish

### **Now Featuring AMCO's PEER Maintenance-Free Gang Bearings**

- Longer Life
- Save up to 25 extra acres per day
- No need for daily relube
- High Strength Ductile Iron Housing
- Used on models: LOF, LTF, F41, J41, F42, F42B, J42, J42B, J42-Fold, F15B, F15, F17, TJ3, Levee Plow

