

# AMCO

## AMCO's revolutionary hydraulically controlled LF6 and LJ6 Levee Plows



- AMCO-exclusive Follow-the-Levee feature that allows gangs to shift independently from the tractor to follow sharply curving levee lines

- Maintenance-Free gang bearings, heavy duty 1-1½" square bore, toggle mounted with wear guards to protect the bearing housing

- A main frame 7" x 4" x 3/8" toolbar and 1½" square, high-carbon, cold-rolled steel axles

- Gang angles that are easily adjustable with pins from 18 to 28 degrees

- A hitch designed to accommodate category II and III hitches for quick couplers and conventional 3-point hitches

- Adjustable, telescoping frames to accommodate narrow or wide-based levees

- A 3" x 8" hydraulic cylinder on each gang to adjust gang tilt from tractor cab (LF6 and LJ6 only)

- High carbon replaceable and adjustable scraper blades with ¾" x 2" heat treated spring steel shanks, mounted to 3" x 2" x 3/8" high carbon angle iron bar with flange lock nuts 5/8" carriage bolts.

- Standard 24" x 1/4" blades with a 10" backup blade on the end blade of each gang

- Standard heavy-duty ductile iron bearing risers, and wear guards.

### The Best Tillage Tools deserve the Best Guarantee

If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back

800.748.9022



AMCOmfg.com