

J41 - Wheel Offset Harrow - General Purpose



- Disc gangs feature maintenance-free bearings with three-year warranty;
 bearings eliminate possibility of contamination and need for re-lubrication.
- Standard equipment includes: 24" x ¼" cutout blades with backup blades immediately behind; an adjustable tongue with jack; adjustable gang angle on both front and rear gangs; 15" x 6" wheels with 6-bolt wheel hubs; 4" x 8" hydraulic cylinder (3,000 PSI) with hoses to tractor.
- High-carbon replaceable and adjustable scraper blades with %"x 2" heat-treated spring steel shanks, mounted to 3"x 2"x %" high-carbon angle iron bars.
- Upgrades for rocky and woody conditions include: spring-loaded shock absorber gang with 24" x ¼" cutout blades and heavy-duty end bells.

Model	Cutting Width	No. of Disc Blades	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs*
J41-1624	70"	15	6	68-88	2,592
J41-1824	7'10"	18	6	74-95	2,739
J41-2024	8'8"	20	6	81-101	2,905
J41-2224	9'6"	22	8	88-108	3,154
J41-2424	10'4"	24	8	95-115	3,345

^{*}To calculate weight/blade, divide the approximate weight of the model by the number of disc blades. Specifications for all models subject to change without notice.

AMCO-Exclusive Product Performance Guarantee

Repair, Replace, or Refund: AMCO Guarantees Performance. The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time,

we'll repair it, replace it or buy it back.



