

AMCO



LF6 & LJ6 - Levee plow

Build levees in fewer passes—save time and money.

Get your field ready for rice with AMCO's revolutionary hydraulically controlled LF6 and LJ6 Levee Plows. These tough tools raise the bar for value, convenience, quality, performance, and durability.

LF6 and LJ6 Hydraulic Levee Plows feature on-the-go gang tilt adjustments, completely controlled from the tractor seat, allowing the operator to reduce the number of passes required and save time and fuel.

AMCO Levee Plows are also available in a manual version with turnbuckles: MLF6 and MLJ6. Both Manual and Hydraulic Levee Plows are available with 9" or 10½" blade spacing and feature reversible gangs so they can tear down as well as build up levees. Cutting weights vary from 216 to 254 pounds per blade depending on the model.

- AMCO-exclusive Follow-the-Levee feature allows gangs to shift independently from the tractor to follow sharply curving levee lines
- Disc gangs feature maintenance-free bearings with three-year warranty; bearings eliminate possibility of contamination and need for re-lubrication
- A main frame 7" x 4" x ½" toolbar and 1½" square, high-carbon, cold-rolled steel axles
- Gang angles easily adjustable with pins from 18 to 28 degrees
- A hitch designed to accommodate category II and III hitches for quick couplers and conventional 3-point hitches
- High carbon replaceable and adjustable blades with 3/8" x 2" heat treated spring steel shanks, mounted to 3" x 2" x 3/8" high carbon angle iron bars with flange lock nuts and 5/8" carriage bolts.
- Adjustable, telescoping frames for narrow or wide-based levees
- Standard 24" x ½" blades with a 10" backup blade on the end blade of each gang

Optional equipment: manual control ratchet jacks, 24" x ½" cutout blades, 26" x ½" cutout blades, 26" x ½" plain blades, feathering blade set (2) with backup blade



PRODUCT PERFORMANCE GUARANTEE—Repair, Replace, or Refund: AMCO Guarantees Performance. The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

Right: Adjustment holes allow the flexibility to build extra narrow or extra wide levees.



Below: The ratchet jack adjusts the cutting width, determining the overall width of the levee.



Above: Pictured is the Manual Levee Plow (Hydraulic Levee Plow also available).



Left: Different blade configurations are available to achieve the desired levee type.



Above: Move gangs forward or back to control the cutting angle.



Above: Gang bolt wrench is included.

Right: Front of the Levee Plow.



AMCO

MANUFACTURING, INC.

800 S. Industrial Parkway
P. O. Box 1107
Yazoo City, MS 39194

Toll free: 800-748-9022
662-746-4464
Fax: 662-746-6825

Web: www.amcomfg.com
Facebook: www.facebook.com/AMCOManufacturingInc
Email: sales@amcomfg.com

Levee Plow Models

Model Hydraulic/ Manual	Adjustable Cutting Width	No. of Discs	Blade Spacing	Approx. Engine HP Required	Approx. Weight lbs.*
LF6-824 MLF6-824	8'11" to 9'11"	8	9"	108-169	2,060
LF6-1024 MLF6-1024	10'5" to 11'5"	10	9"	122-203	2,260
LF6-1224 MLF6-1224	11'11" to 12'11"	12	9"	137-238	2,460
LJ6-824 MLJ6-824	9'5" to 10'5"	8	10½"	115-189	2,160
LJ6-1024 MLJ6-1024	11'1" to 12'1"	10	10½"	135-216	2,360
LJ6-1224 MLJ6-1224	12'9" to 13'9"	12	10½"	155-243	2,560

*To calculate weight loads, divide the approximate weight of the model by the number of disc blades. Specifications for all models subject to change without notice.

SINCE
1947

**TOUGH
TILLAGE
TOOLS**

AMCO121