

F15 - Double Offset Tandem Harrow



- Double Offset Tandem design – overlapping front discs without the need for a center shank to level off the center.
- Folding Flexwings to follow the contour of the field.
- 9" blade spacing.
- Standard 24"x1/4" Plain blades.
- Welded steel spacer spools to prevent breakage upon impact with solid obstacles such as rocks.
- 1.5" square axles.
- Main frames featured boxed, all-welded steel tubing.
- 17 degree gang angle. No adjustment necessary.
- Standard light kit, safety chains, & SMV emblem.
- DIAL-A-DEPTH control ensures an even cutting depth.
- Front Depth Gauge Wheels to assist with controlled depth of the wings.
- Standard heavy-duty ductile iron bearing risers and wear guards.
- 3/16" x 6 1/2" x 8", high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2 1/2" x 2 1/2" square tubing. The scrapers are attached to the 2 1/2" x 1/2" thick arms with heavy-duty u-bolts.
- AMCO's Peer Maintenance Free gang bearings - No need for daily relube.

F15 Heavy Duty

Model	Cutting Width	Transport Width	Transport Height	No. of Disc Blades	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs*
F15-6624	24'0"	14'6"	11'0"	66	20	243-297	11,591
F15-7424	27'0"	14'6"	12'	74	22	243-297	12,283
F15-8224	30'0"	14'6"	13'3"	82	22	256-318	12,935

NOTE: 15 x 10 8-hole wheels and 8-hole hubs optional equipment on F15-66 blade, 74 blade, and 82 blade (center section only).

F15 Giant

Model	Cutting Width	Transport Width	Transport Height	No. of Disc Blades	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs*
F15-9424	34'6"	17'6"	14'0"	94	26	310-378	15,423
F15-10624	39'0"	17'6"	15'9"	106	30	337-405	16,671

NOTE: 15 x 10 8-hole wheels and 8-hole hubs standard equipment on F15-94 blade and 106 blade (center section only).

*To calculate weight per blade on each unit, divide the approximate weight by the number of blades. Specifications for all models subject to change without notice.

AMCO-Exclusive Product Performance Guarantee

Repair, Replace, or Refund: AMCO Guarantees Performance. The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it or buy it back.