

F41 - 9" Wheel Offset Harrow - General Purpose









- Disc gangs feature maintenance-free bearings with three-year warranty; bearings eliminate possibility of contamination and need for re-lubrication.
- Standard equipment includes: 22" x 1/4" cutout blades; an adjustable tongue with jack; adjustable gang angle on both front and rear gangs; 15"x 6" wheels with 6-bolt wheel hubs; 4" x 8" hydraulic cylinder (3,000 PSI) with hoses to tractor.
- High-carbon replaceable and adjustable scraper blades with 3/4" x 2" heat-treated spring steel shanks, mounted to 3" x 2" x 3%" high-carbon angle iron bars.
- Upgrades for rocky and woody conditions include: spring-loaded shock absorber gang with 24" x 1/4" cutout blades and heavy-duty end bells.
- Safety features include safety chains, slow-moving placard, and light kits.
- Optional equipment includes feathering blades with scraper for the rear gang.

Model	Cutting Width*	No. of Disc Blades	No. of Bearings	Approx. Engine HP	Approx. Weight lbs**
F41-1822	6'9"	18	6	68-88	2,428
F41-2022	7'6"	20	6	75-95	2,568
F41-2222	8'3"	22	8	81-101	2,801
F41-2422	9'0"	24	8	88-108	2,922
F41-2622	9'9"	26	8	95-115	3,036
F41-2822	10'6"	28	8	101-122	3,257

^{*}Transport width is cutting width plus 6".

Specifications for all models subject to change without notice.

AMCO-Exclusive Product Performance Guarantee

- MAC - MAC

Repair, Replace, or Refund: AMCO Guarantees Performance. The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it or buy it back.



^{**}To calculate weight/blade, divide the approximate weight of the model by the number of disc blades.