

# AMCO

MANUFACTURING, INC.



## D41 WHEEL OFFSET HARROWS

### Big performance tillage tools for smaller operations

AMCO's tough, dependable D41 Wheel Offset Harrow with 9" blade spacing offers the same rugged build and versatility as larger AMCO tools. Designed for use with 34 to 95 horsepower tractors, this model is perfect for residential gardens, commercial landscaping, and seedbed preparation for food plots.

#### FEATURES

- › Six triple-lip sealed greaseable 1 $\frac{1}{8}$ " bearings with a two-year warranty
- › Adjustable gang angles on both front and rear gangs
- › 15" x 16" wheels with 6-bolt wheel hubs
- › 3" x 8" hydraulic cylinder with stroke control
- › 1 $\frac{1}{8}$ " square high-carbon, cold-rolled, finished steel axles
- › Safety chains included
- › Tongue can be adjusted to an offset position
- › Choose 18", 20", or 22" blades with adjustable high-carbon steel scrapers
- › Cutting widths range from 6' to 9' depending on model
- › Weight ranges from 1,867 pounds to 2,402 pounds depending on model
- › Powder-coated finish for enhanced durability
- › Optional equipment includes cutout blades in place of plain blades or feathering blades for rear gang



**PRODUCT PERFORMANCE GUARANTEE—Repair, Replace, or Refund: AMCO Guarantees Performance.** The best tillage tools deserve the best guarantee. The AMCO guarantee is simple. If, during the first 30 days, your AMCO equipment doesn't perform as promised, and if we don't make it perform in a reasonable amount of time, we'll repair it, replace it, or buy it back.

*Below: Tongue position adjustment lets you set up the D41 for varying equipment and field conditions, while the stabilizer spring is adjustable for leveling the harrow.*



*Above: Hydraulic cylinder has stroke control for cutting depth adjustment. The transport lockout can be secured for highway transportation.*



*Left: Front and rear gang angle can be adjusted from 17 to 23 degrees.*



*Above: The D41 comes standard with high-carbon steel scraper blades on ½" x 1½" shanks mounted on 2" x 2" angle iron bars.*



## MANUFACTURING, INC.

800 S. Industrial Parkway  
P. O. Box 1107  
Yazoo City, MS 39194

Toll free: 800-748-9022  
662-746-4464  
Fax: 662-746-6825

Web: [www.amcomfg.com](http://www.amcomfg.com)  
Facebook: [www.facebook.com/AMCOManufacturingInc](http://www.facebook.com/AMCOManufacturingInc)  
Email: [sales@amcomfg.com](mailto:sales@amcomfg.com)

## D41 Wheel Offset Harrow Models

Model	Cutting Width*	No. of Discs	No. of Bearings	Approximate Engine HP Required	Approximate Weight lbs**
D41-1622	6'0"	16	6	34-54	1,867
D41-1822	6'9"	18	6	41-61	1,952
D41-2022	7'6"	20	6	47-68	2,102
D41-2222	8'3"	22	6	61-81	2,252
D41-2422	9'0"	24	8	74-95	2,402

\*Transport width is cutting width plus 6"

\*\*To calculate weight/blade, divide the approximate weight of the model by the number of disc blades. Specifications subject to change without notice.



**TOUGH  
TILLAGE  
TOOLS**