

# Z-BLADE



MANUFACTURING, INC.

## A versatile grader blade for road work and ag operations.

AMCO's innovative Z-Blade is designed for both road maintenance and farm work. Featuring dual-edged cutting blades and tall side pans that keep material from overflowing, the Z-Blade can fix potholes and washouts. The unit can also level roads, driveways, and parking lots.

On farmland, the Z-Blade can be used to smooth out ruts in turn rows, resulting in better soil conditions, a smoother ride for planters, and more uniform planting conditions.

The Z-Blade is specially built to eliminate washboarding and does not leave behind windrows.

*See reverse for additional information.*



Z-8 model shown above.

## The Z-Blade Features

- › Available in 8', 10', 12', and 14' working widths
- ›  $\frac{1}{2}$ " x 6" high-carbon, heat-treated blades are reversible and replaceable
- › Standard 3-point hitch fits category II or III hitches and is quick-hitch compatible
- › Features a powder-coated finish
- › Equipped with tall side pans with depth adjustment
- › Replaceable skid plates are 3" wide x  $\frac{3}{8}$ " thick
- › Frame is constructed of 4" x 4" x  $\frac{3}{8}$ " steel tubing



MANUFACTURING, INC.



The **Z-Blade** cuts out high spots and fills low spots. Material builds up on the front blade, then flows up and over the rear blade, spreading evenly for a smooth and level finish grade.

## TOUGH TILLAGE TOOLS



Toll free: 800-748-9022

Web: [www.amcomfg.com](http://www.amcomfg.com)

Local: 662-746-4464

Facebook: [www.facebook.com/AMCOManufacturingInc](https://www.facebook.com/AMCOManufacturingInc)

Fax: 662-746-6825

Email: [sales@amcomfg.com](mailto:sales@amcomfg.com)

800 S. Industrial Parkway | P. O. Box 1107 | Yazoo City, MS 39194

## More AMCO Z-Blade Features



Fabricated steel side pans with depth adjustment.



Both the dual-edged cutting blades and the skid plates that run along the bottom of the side pans are replaceable.



The unit is quick-hitch compatible, fitting category II or III hitches.

## Z-Blade Models

Model	Working Width	Approx. Maximum Engine HP	Approx. Weight lbs.
Z-8	8'	90	1,025
Z-10	10'	100	1,195
Z-12	12'	110	1,460
Z-14	14'	120	1,630

Specifications subject to change without notice.