

VERTICAL AND OFFSET ROTARY DITCHERS

From coupler to cutter head, AMCO makes a better Ditcher.

AMCO's industry-leading ditchers are ideal for cleaning roadside ditches or directing water away from crops. Our ditchers are built with the pride in workmanship AMCO is known for.

All AMCO Ditcher models offer:

- Case-hardened dual 80 heavy-duty chain with 16-tooth and 22-tooth drive sprockets
- Series 55 PTO drivelines with shear bolt protection
- A two-year bearing warranty
- Reversible cutting blades for longer life
- Concave skid shoe design with quick-adjust ratchet for better tracking and more uniform ditch
- A powder-coated finish that is more durable and environmentally friendly
- A ripper shank to loosen tough soils and prolong bearing life

See reverse for Offset Ditcher information.



MANUFACTURING, INC.



Original Vertical Ditcher -

High-performing in dry conditions, the original Vertical Rotary Ditcher features center cutter head placement and straddles the ditch during cleanout.



Dominator

NEW! Dominator Vertical Ditcher -

The heavy-duty Dominator is a perfect fit for larger horsepower tractors.

Original Vertical and Dominator Spec Comparison

Feature	Original Vertical Rotary Ditcher	Dominator Vertical Rotary Ditcher
Power Requirements		
PTO driveline	540 (1½" 6-spline), small 1,000 (1½" 21-spline), and large 1,000 (1½" 20-spline)	Small 1,000 (1½" 21-spline), and large 1,000 (1½" 20-spline)
Tractor engine horsepower range	60–150	80–200
Specs		
Ditcher body casing	10" x 6" x 29"	14" x 10" x 36"
Weight	563–736 lbs.	850 lbs.
5-blade cutter head	18"–20" or 24"–26"	24"–26"
Frame		
Maintenance casing access	Top and bottom of ditcher	Top and side of ditcher
Hitch	Flat steel 3-point hitch frame Compatible with category II and III 3-point hitches	All-tube steel 3-point hitch (standard transportation loop welded to top of hitch) Compatible with category II and III 3-point hitches
Ripper shank brackets	Flat steel brackets	2" x 3" tube steel brackets



Offset Ditcher - Delivering outstanding performance in wet conditions, the Offset Ditcher has the ability to dig drainage ditches for any crop or soil type. The cutter head sits behind the left tractor tire, leaving only the right tire track alongside the ditch—no need to straddle the ditch.

Offset Ditcher Specs

Feature	Offset Rotary Ditcher
Power Requirements	
PTO driveline	540 (1½", 6-spline), small 1,000 (1½", 21-spline), and large 1,000 (1½", 20-spline)
Tractor engine horsepower range	60–150
Specs	
Ditcher body casing	10" x 6" x 58"
Weight	734–901 lbs.
5-blade cutter head	18"–20" or 24"–26"
Frame	
Maintenance casing access	Top and bottom of ditcher
Hitch	Flat steel 3-point hitch frame Compatible with category II and III 3-point hitches
Ripper shank brackets	Flat steel brackets

More AMCO Ditcher Features



All cutter heads feature five blades for a cleaner, more uniform ditch. Blades are reversible and replaceable for longer life.



Ripper shank loosens tough soils to prolong bearing life. Standard on all models.



A lift hook feature on the Dominator makes it easy to attach a chain or strap for extra maneuverability when loading.



Concave skid shoe with quick-adjust ratchet gives better tracking for a more uniform ditch. Standard on all models.



All ditcher models feature PTO drive shaft parking hook to secure PTO for storage.



The Dominator features side access for maintenance.

TOUGH TILLAGE TOOLS



Toll free: 800-748-9022

Web: www.amcomfg.com

Local: 662-746-4464

Facebook: www.facebook.com/AMCOManufacturingInc

Fax: 662-746-6825

Email: sales@amcomfg.com

800 S. Industrial Parkway | P. O. Box 1107 | Yazoo City, MS 39194