

F17 DOUBLE OFFSET TANDEM DISC HARROW

Built AMCO tough for seedbed preparation.

Since each farming operation is different, AMCO's Double Offset Tandem Disc Harrow is available in a wide variety of sizes. Weighing between 296 and 337 pounds per cutting foot, this disc harrow is available in 9'3", 10'6", 12'0", 13'6", 15'0", and 16'6" models for use with tractors ranging from 68 to 176 engine horsepower.

High-quality features are essential in today's farming operation, and the F17 won't disappoint.

See reverse for additional information.



**Maintenance-Free
Gang Bearings**



MANUFACTURING CO.



Model shown above: F17-3822



Scan to
visit the F17
product page.

The F17 Disc Harrow Features

- › Disc gangs feature maintenance-free bearings with three-year warranty; bearings eliminate possibility of contamination and need for re-lubrication
- › Wear guards protect bearing housing
- › Features 1½" square, high-carbon, cold-rolled steel axles
- › Includes 70" long pull tongue with tongue jack and reversible clevis
- › Features adjustable gang angle
- › Equipped with ¾" x 6½" x 8" high-carbon steel, replaceable, adjustable scraper blades mounted on bars of 2½" x 2½" square tubing; the scrapers are attached to the 2½" x ½" thick arms with heavy-duty U-bolts
- › Features standard 22" x ¼" plain blades on 9" spacing
- › Comes standard with gang bolt wrench, light kit, and 4" x 8" (3,000 PSI) hydraulic cylinder with stroke control and hose bundle to tractor

Dealing with unexpected or unpredictable terrain? Try the optional Shock Absorber Bearing Riser, which allows the gang on the harrow to move upward and back to relieve shock when the disc blades encounter an obstacle in the ground.

Other customization options include dual wheels in place of single wheels and cutout blades in place of the standard plain blades. More blade configurations are available as well—call to discuss your options.



MANUFACTURING CO.



The **F17** opens and breaks up the soil surface, smoothing the soil so your ideal seedbed is ready for planting.

TOUGH TILLAGE TOOLS



Toll free: 800-748-9022

Web: www.amcomfg.com

Local: 662-746-4464

Facebook: www.facebook.com/AMCOManufacturingCo

Fax: 662-746-6825

Email: sales@amcomfg.com

800 S. Industrial Parkway | P. O. Box 1107 | Yazoo City, MS 39194

More AMCO F17 Features



Front-to-rear leveling spring allows easy adjustment in the field. The standard tongue jack and gang bolt wrench both fit in place on the tongue during operation. A 4" x 8" (3,000 PSI) hydraulic cylinder with hoses to the tractor is also standard equipment.



4" x 8" (3,000 PSI) hydraulic cylinder with transport lockout pin ensures safe road travel. Hoses, light kit, and safety chain are also standard equipment.



For unexpected or unpredictable terrain, try the optional Shock Absorber Bearing Riser. The gang will move upward and back to relieve shock when the blades strike an obstacle.



Diminishing blades on the rear gang provide a smooth, even cut.



Standard heavy-duty scrapers with replaceable high-carbon blades free blades of soil buildup.

F17 Double Offset Tandem Disc Harrow Models

Model	Cutting Width	No. of Discs	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs.*
F17-2622	9'3"	26	8	68-101	3,414
F17-3022	10'6"	30	8	81-108	3,698
F17-3422	12'0"	34	8	95-122	3,982
F17-3822**	13'6"	38	12	108-135	4,816
F17-4222**	15'0"	42	12	122-155	5,130
F17-4622**	16'6"	46	12	142-176	5,644

*To calculate weight/blade, divide the approximate weight of the model by the number of disc blades.

**Includes 2 outrigger bars, clamps, and dual 9.5L tires on 15" x 8" wheels.

Specifications subject to change without notice.