

D41 WHEEL OFFSET HARROW

High-performing tillage tools for smaller operations.

AMCO's tough, dependable D41 Wheel Offset Harrow with 9" blade spacing offers the same rugged build and versatility as larger AMCO tools. Designed for use with 34 to 95 horsepower tractors, this model is perfect for residential gardens, commercial landscaping, and seedbed preparation for food plots.

See reverse for additional information.



Greaseable Triple-Lip Sealed Bearings With Sleeve Reinforcement
(Two-Year Warranty)



MANUFACTURING CO.



Scan to
visit the D41,
F41, & F42
product page.

Model shown above: D41-2222

The D41 Wheel Offset Harrow Features

- › Triple-lip sealed, regreaseable 1 $\frac{3}{4}$ " round bearings come with a two-year warranty
- › Designed with adjustable gang angles on both front and rear gangs
- › Two 9.5L tires on 15" x 6" wheels with 6-bolt hubs
- › Equipped with 3" x 8" hydraulic cylinder
- › Features 1 $\frac{1}{8}$ " square, high-carbon, cold-rolled, finished steel axles
- › Safety chains, tongue jack, and hydraulic hoses included
- › Tongue can be adjusted to an offset position
- › Choose 18", 20", or 22" blades with adjustable high-carbon steel scrapers
- › Cutting widths range from 6'0" to 9'0", depending on model
- › Weight ranges from 1,867 pounds to 2,402 pounds, depending on model
- › Features a powder-coated finish for enhanced durability
- › Optional equipment includes cutout blades in place of plain blades and feathering blade attachment for rear gang



MANUFACTURING CO.



The **D41** cuts and sizes residue, eliminates clumps, and loosens packed soil for optimal results.

More AMCO D41 Features



The D41 comes standard with high-carbon steel scraper blades on ½" x 1½" shanks mounted on 2" x 2" angle iron bars.



Tongue position adjustment lets you set up the D41 for varying equipment and field conditions, while the tongue control rod is adjustable for leveling the harrow.



Front and rear gang angle can be adjusted from 17° to 23°.

TOUGH TILLAGE TOOLS



Toll free: 800-748-9022

Web: www.amcomfg.com

Local: 662-746-4464

Facebook: www.facebook.com/AMCOManufacturingCo

Fax: 662-746-6825

Email: sales@amcomfg.com

800 S. Industrial Parkway | P. O. Box 1107 | Yazoo City, MS 39194



3" x 8" hydraulic cylinder. The transport lockout can be secured for highway transportation.

D41 Wheel Offset Harrow Models

Model	Cutting Width*	No. of Discs	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs.**
D41-1622	6'0"	16	6	34-54	1,867
D41-1822	6'9"	18	6	41-61	1,952
D41-2022	7'6"	20	6	47-68	2,102
D41-2222	8'3"	22	6	61-81	2,252
D41-2422	9'0"	24	8	74-95	2,402

*Transport width is cutting width plus 6".

**To calculate weight/blade, divide the approximate weight of the model by the number of disc blades. Specifications subject to change without notice.