

LOF LIFT OFFSET HARROW



MANUFACTURING CO.



Model shown above: LOF-2424

Built AMCO tough for almost 70 years.

AMCO's LOF Lift Offset Harrows are perfect for building and maintaining food plots, logging roads, gardens, turn rows, and firebreaks, as well as seedbed preparation, pivot turn management, and much more. The LOF comes in three cutting widths: 7'6", 8'3", and 9'0". It weighs up to 2,392 pounds. The LOF Harrow will outlast the competition.

See reverse for additional information.

The LOF Lift Offset Harrow Features

- › Disc gangs feature maintenance-free bearings with three-year warranty; bearings eliminate possibility of contamination and need for re-lubrication
- › Optional Shock Absorber Bearing Risers to relieve shock when disc blade encounters obstacles
- › Standard heavy-duty scrapers with replaceable high-carbon blades free blades of soil buildup
- › Designed with 3" x 4" x 1/4" rectangular tubing on the main frame and 3" x 5" x 1/4" on the gang frame
- › Features 1 1/2" square, high-carbon, cold-rolled steel axles
- › Standard 3-point hitch fits category II or III hitches and is quick-hitch compatible
- › Equipped with standard 24" x 1/4" cutout blades on 9" spacing with 2" step-down blades on right front and right rear
- › Gang angles on the front and rear adjust 14° to 18° to adapt to any soil conditions
- › Features a powder-coated finish
- › Optional bolt-on attachment feathering blade adds smoother finish at faster speeds
- › Wear guards protect bearing housing



**Maintenance-Free
Gang Bearings**



MANUFACTURING CO.



The **LOF** is a rugged, hardworking harrow that is perfect for food plots, logging roads, gardens, turn rows, and more.

More AMCO LOF Features



Axle size and bearings are identical to those on the AMCO 39' disc harrow, ensuring this harrow is bulletproof.



Heavy-duty 3-point hitch with reversible $1\frac{1}{2}$ " lower hitch pin fits category II and III hitches and is quick-hitch compatible.



Each front and rear gang has four ductile iron bearing risers to eliminate axle failure and add strength. Scrapers ensure your dirt stays in the field—not between your blades.

TOUGH TILLAGE TOOLS

SINCE
1947

Toll free: 800-748-9022

Web: www.amcomfg.com

Local: 662-746-4464

Facebook: www.facebook.com/AMCOManufacturingCo

Fax: 662-746-6825

Email: sales@amcomfg.com

800 S. Industrial Parkway | P. O. Box 1107 | Yazoo City, MS 39194



AMCO's gang frame is strong because we use 3" x 4" x $\frac{1}{4}$ " rectangular tubing on the main frame and 3" x 5" x $\frac{1}{4}$ " on the gang frame. A spring-loaded leveling system adds strength and durability to the hitch, making it ideal for stubble cutting and compacted soil conditions.



A gang angle located on each corner adjusts 14° to 18° front and rear to make your cut as aggressive as needed.

LOF Lift Offset Harrow Models

Model	Cutting Width	No. of Discs	No. of Bearings	Approx. Engine HP Required	Approx. Weight lbs.*
LOF-2024	7'6"	20	8	70	2,152
LOF-2224	8'3"	22	8	80	2,272
LOF-2424	9'0"	24	8	90	2,392

*To calculate weight/blade, divide the approximate weight of the model by the number of disc blades. Specifications subject to change without notice.