

Z-BLADE



MANUFACTURING CO.

A versatile grader blade for road work and ag operations.

AMCO's innovative Z-Blade is designed for both road maintenance and farm work. Featuring dual-edged cutting blades and tall side pans that keep material from overflowing, the Z-Blade can fix potholes and washouts. The unit can also level roads, driveways, and parking lots.

On farmland, the Z-Blade can be used to smooth out ruts in turn rows, resulting in better soil conditions, a smoother ride for planters, and more uniform planting conditions.

The Z-Blade is specially built to eliminate washboarding and does not leave behind windrows.

See reverse for additional information.



Model: Z-7



Model: Z-10



Scan to visit the Z-Blade product page.

The Z-Blade Features

- › Available in 6'0", 7'0", 8'0", 10'0", 12'0", and 14'0" working widths
- › Equipped with tall side pans with depth adjustment
- › $\frac{1}{2}$ " x 6" high-carbon, heat-treated blades are reversible and replaceable
- › Replaceable skid plates are 3" wide x $\frac{3}{8}$ " thick
- › Standard 3-point hitch fits category I, II, or III hitches and is quick-hitch compatible
- › Frame is constructed of 4" x 4" x $\frac{3}{8}$ " steel tubing
- › Features a powder-coated finish
- › **Optional equipment:** Scarifiers with hardware for Z-6 and Z-7; skid steer universal adapter for Z-7



MANUFACTURING CO.



The **Z-Blade** cuts out high spots and fills low spots. Material builds up on the front blade, then flows up and over the rear blade, spreading evenly for a smooth and level finish grade.

More AMCO Z-Blade Features



Fabricated steel side pans with depth adjustment.



Optional scarifiers with hardware are available for the Z-6 and Z-7.



Optional skid steer universal adapter is available for the Z-7.

TOUGH TILLAGE TOOLS



Toll free: 800-748-9022

Web: www.amcomfg.com

Local: 662-746-4464

Facebook: www.facebook.com/AMCOManufacturingCo

Fax: 662-746-6825

Email: sales@amcomfg.com

800 S. Industrial Parkway | P. O. Box 1107 | Yazoo City, MS 39194



Both the dual-edged cutting blades and the skid plates that run along the bottom of the side pans are replaceable.



All units are quick-hitch compatible. The Z-6 and Z-7 fit category I or II hitches. All other units fit category II or III hitches.

Z-Blade Models

Model	Working Width	Approx. Maximum Engine HP	Approx. Weight lbs.	Tractor Hitch
Z-6	6'0"	70	735	Category I & II
Z-7	7'0"	80	905	
Z-8	8'0"	90	1,075	Category II & III
Z-10	10'0"	100	1,245	
Z-12	12'0"	110	1,520	
Z-14	14'0"	120	1,690	

Specifications subject to change without notice.